

江西中彦动力设备有限公司

JIANGXI ZHONGYAN POWER EQUIPMENTS CO.,LTD.

Room 601, Greenland Zifeng building, 3333 Ziyang Avenue,
Nanchang, Jiangxi, China

0086-791-88216612

0086-138-0704-7811

jjzhongyan@163.com

0086-138-0704-7811

**EXCELLENT POWER
MADE IN ZHONG YAN!**

卓越动力，中彦制造！

中彦动力
ZHONGYAN POWER



JIANGXI ZHONGYAN POWER EQUIPMENTS CO.,LTD.

卓 越 动 力 中 彦 制 造

excellent power made in zhong yan

Excellent Power Made In Zhong Yan

卓越动力，中彦制造！

江西中彦动力设备有限公司

JIANGXI ZHONGYAN POWER EQUIPMENTS CO.,LTD.

目录 | Contents

| | |
|---------------------------------|-------|
| 公司简介 Company Profile..... | 06 |
| 主营业务 Main Products..... | 08 |
| 资质认证 Certification..... | 10 |
| 品质保证 Quality Guarantee..... | 11 |
| 企业文化 Culture..... | 12 |
| 核心价值观 Core Value..... | 12 |
| 产品介绍 Product Introduction..... | 13-32 |
| 移动电站 Automobile Generation..... | 33-36 |
| 配套电气柜 Electrical Cabinet..... | 37-38 |
| 全面服务 Full Service..... | 39 |
| 服务流程 Service Process..... | 40 |
| 零配件服务 Parts Service..... | 41 |
| 租赁服务 Rental Service..... | 42 |
| 客户服务 Customer Service..... | 43 |
| 服务网络 Service Network..... | 44 |
| 合作伙伴 Cooperative partner..... | 46 |



卓越动力 中彦制造

江西中彦动力设备有限公司创办于2014年3月，注册资金1000万元，公司地址位于江西省南昌市。

主要经营：国内外船用陆用发动机、发电机及机组、自动化控制系统、智能柴油机应急/消防水泵、空气能热泵、环保工程、高低压柜、变压器以及进口及国产装机配件、电线、电缆等产品，并提供后续服务。公司本着“客户至上，诚信第一”的原则，得到广大客户的一致好评，在同行业中创造了良好的口碑。我们本着：“薄利多销、互惠互利”的经营理念，不断拓宽业务，取得了较好的经济效益。

EXCELLENT POWER MADE IN ZHONG YAN

Jiangxi Zhong Yan Power Equipment Co., Ltd. was founded in March 2014, with a registered capital of 10 million yuan. The company's address is located in Nanchang, Jiangxi. Main business: domestic and foreign marine engine, generator and unit, automatic control system, intelligent diesel engine emergency / fire pump, air energy heat pump, environmental protection engineering, high and low pressure cabinet, transformer and imported and domestically installed accessories, wires, cables and other products, and provide follow-up services. In line with the principle of "customer first, integrity first", the company has won favorable comments from all customers and has created a good reputation in the same industry. In line with the management concept of "small profits but quick turnover and mutual benefit", we have continuously expanded our business and achieved better economic results.

主营业务/ Main products

中彦动力有限公司与多家柴油发动机、发电机、控制系统和相关设备厂家有代理合作协议，功率覆盖3—3000KW的柴油发电机组。

柴油机、发电机、电机控制柜、变压器、电子产品、仪器仪表、机械设备及配件的销售、维修、技术咨询、售后服务。

The sales, maintenance, technical consultation and after-sales service of diesel engine, generator, motor control cabinet, transformer, electronic product, instrument and instrument, mechanical equipment and accessories.

1

电线电缆、五金交电、建材的销售、技术咨询、售后服务。

Wire and cable, hardware, electricity, building materials sales, technical consultation, after sales service.

2

环保工程

Environmental protection engineering

3

自营和代理各类商品和技术的进出口业务。

Import and export business of all kinds of commodities and technologies.

4

计算机软硬件的技术研发、技术咨询、技术转让、技术服务。

Computer software and hardware technology research and development, technical consulting, technology transfer, technical services.

5

在产品资源上，不断加强监督力度，产品的质量得到了有力的保障，与众多国有大型公司都保持着良好的供求关系，如：无锡动力、玉柴机器、东风康明斯、西安康明斯、重庆康明斯、德国奔驰（MTU）、英国帕金斯、瑞典沃尔沃、瑞典斯堪尼亚、上柴股份、泰豪科技、江苏恒通、上海乾能、上海凯讯、上海马拉松、康富科技（原三波电机）、中国重汽、上海孚创等。厂家在确保产品的同时供求及时，遵守信用，双方均能按合同履行各自的权益和义务，利益与风险共享，既保持了产品的价格优势，又保证了产品质量，达到双赢的目的。

On the product resources, continuous strengthening of supervision, the quality of the product has been strongly guaranteed, and many large state-owned companies have maintained good supply and demand relations, such as Wuxi power, Yulai machinery, Dongfeng Cummings, Xi'an Cummings, Chongqing Cummings, German Benz (MTU), British Perkins, Sweden Walter. Waugh, Swedish stean, Shanghai stock, Thai science and technology, Jiangsu Hengtong, Shanghai dry, Shanghai Kaixun, Shanghai marathon, Kangfu science and Technology (the original three wave motor), China heavy steam, Shanghai Fu Chuang and so on. In order to ensure the product, the supply and demand are timely and the credit is observed. Both sides can fulfill their respective rights and obligations according to the contract, share the interests and risks, keep the price advantage of the products, and ensure the quality of the products, and achieve the win-win goal.

资质证书/ Certification



品质保证/ Quality Assurance

江西中彦动力设备有限公司对所提供的产品均确保其原装原产正品货物，保证产品质量的可靠。凡由江西中彦动力设备有限公司提供的各型发电设备，均提供保修：自交货之日起15个月或机组调试完成之日起12个月或机组运行1000小时内（三者以先到时间为准）。

ZYPOWER guarantee that all products are manufactured by the original manufacturer with steady quality. All power generation equipments supplied by ZYPOWER provides a warranty: 15months after delivery, 12months after commission or 1000hours running, whichever firstly.



原材料由品检员进行来料检验，并形成详细的检验记录。发现不合格，按照采购管理制度和不合格品处理程序进行处理。

生产过程的制程检验，包括钣金、总装、电装、调试、喷涂等工序，并形成详细的检验记录。发现不合格，要采取预防和纠正措施，并严格按照不合格品处理程序进行处理。

机组测试由专业人员通过先进、完善的专用测试设备进行。测试结果由电脑自动记录，达不到国家标准规定的出厂要求时，要再次进行调整和调试，确保机组技术参数完全符合国家标准。

成品入库前，由品检员按照成品检验标准逐项检验，并形成详细的检验记录。只有合格品才能入库。

All raw and processed material must be inspected and made relative inspection record. Any disqualification must be transacted according to the purchasing regulation and solution procedure of the reject.

Inspection during the production, include the assembly procedure, electricity packs service procedure, debugging procedure, paint procedure and so on. All procedure has its record. Any disqualification must be transacted according to the solution procedure of the reject and taking steps to prevent and correct the same disqualification.

To ensure all technical parameter of the genset is accord with the national standard, all genset must be tested by the professional personnel and advanced and special testing equipment, and the test result will be recorded automatically by the computer.

QCE have to check all the finished products item by item and make particular inspection record according to the inspection standard of the finished products before warehousing.

激发员工潜能，团结协作，共创辉煌 不断创新，与客户共同协作，确保双赢

Develop the potential of staff, solidarity and coordination, create resplendence
Continuous innovation, mutually cooperate with customers to ensure the win-win situation.

核心价值观/ Core Value

以人为本 People-oriented

人是万物之王，人的价值高于物的价值，员工是企业最重要的资源。

People are the king of all things, people's value is higher than the value of things, and the employees are the most important resource of company.

团队精神 Team Spirit

共同价值高于个人价值，任何事业都是与人协作的结果。

Common value is higher than personal value. All business is the result of collaboration with other people.

追求卓越 Striving for Excellence

个人与企业取得的成就永远不能超过他的期望，不争第一的企业不是优秀的企业。

The achievements of individuals and enterprises can never be exceeded his expectations, an enterprise which doesn't want vied for the number one is not a good enterprise.

诚信经营 Credit management

市场经济是信用经济，不守信用的企业，其生命力也不会长久，不守诚信的人，是没有价值的人。

Market economy is a credit economy, vitality of the enterprise which always breaking their words will not last long, people are valueless who always make empty promises.

创新与变革 Innovation and Revolution

不变是暂时的，变化是永恒的，“变则通，通则久”。

Unchanged is temporary, changed is eternal, "Changed to pass, long General".

以客户为导向，以服务为核心 Customer-oriented, take service as the core

客户是企业的衣食父母，为客户提供专业的服务，满足客户需求，是我们的职责。

Customer is the god of the enterprise, it is our responsibility to provide professional services and meet the demand of the customers.



无动系列 柴油发电机组

WUDONG SERIES

品牌介绍 / Brand

无动系列柴油发电机组是我公司采用无锡动力工程股份有限公司研制生产的万迪牌135/138系列新品柴油机，配置名牌发电机组而成。无动万迪柴油机选用高供速率的P型高压油泵与多孔低贯量喷油器匹配，使油机功率更大、综合性能更优良。功率从100KW-1200KW近20多个功率档不同功能的柴油发电机组，让客户有更大的选择余地。

Wudong series diesel generator set adopts dhabi brand new diesel engine from wuxi power engineering Co,LTD,and famous alternator.Wudong dhabi diesel engine selects high fuel supply rate of P type high pressure pump and porous low penetration quantity injector,that makes oil machine power matching larger,superior comprehensive performance.Power range of diesel generator set from 100KW to 1200KW is about more than 20 different power function,which makes customers have more choices.

| | |
|-------------|--------------------|
| 标准配置 | Standard equipment |
| 可选配置 | Optional equipment |

标准配置

发动机
启动免维护蓄电池及蓄电池连接线
40°C散热水箱
工业消声器、波纹
发电机
输出断路器
智能控制屏
钢式底架

Standard equipment

Diesel engine
Starting batteries and battery connect wires
40°C water cooled radiator
Silencer and flexible exhaust hose
Alternator
Output circuit breaker
Digital control panel
Steel base frame

可选配置

静音箱
全自动控制系统
50°C散热水箱
水套加热器
自动并机柜控制系统

Optional equipment

Sound proof
ATS
50°C Water cooled radiator
Water heater
Automatic parallel synchronizing control system

规格参数 / Specifications

| 机组型号 (Model) | 功率Power KW KVA | 电流A Current | 发动机型号 Engine model | 缸数 Cyinder | 缸径*行程 Bore*Stroke | 排气量L Displacement | 机油容量L Lube oil | 油耗g/kw.h Consumption | 尺寸mm SIZE | 重量Kg Weight |
|-----------------|-------------------|----------------|-----------------------|---------------|----------------------|----------------------|-------------------|-------------------------|----------------|----------------|
| ZY-50GF | 50 62.5 | 90 | WJ43TD6 | 4 | 105*125 | 3.6 | 12 | 215 | 1850*760*1300 | 850 |
| ZY-60GF | 60 75 | 108 | WJ45TAD7 | 4 | 105*130 | 3.6 | 15 | 215 | 2250*800*1500 | 1200 |
| ZY-75GF | 75 93.75 | 135 | WJ65TD8 | 6 | 105*125 | 3.6 | 16 | 215 | 2250*800*1500 | 1320 |
| ZY-100GF | 100 125 | 180 | WJ68TAD11 | 6 | 105*130 | 3.6 | 16 | 215 | 2300*800*1500 | 1410 |
| ZY-150GF | 150 187.5 | 270 | WJ78TAD17 | 6 | 113*130 | 3.6 | 16 | 215 | 2550*880*1500 | 1530 |
| ZY-220GF | 220 275 | 396 | WJ97ATD24 | 6 | 126*130 | 3.6 | 26 | 215 | 2800*1000*1800 | 1800 |
| ZY-220GF | 220 275 | 396 | WD129TAD23 | 6 | 135*150 | 12.9 | 28 | 217 | 3000*1100*1750 | 2200 |
| ZY-250GF | 250 312.5 | 450 | WD129TAD25 | 6 | 135*150 | 12.9 | 28 | 217 | 3000*1100*1750 | 2250 |
| ZY-280GF | 280 350 | 504 | WD135TAD28 | 6 | 138*150 | 13.5 | 28 | 221 | 3200*1400*1800 | 3400 |
| ZY-300GF | 300 375 | 540 | WD145TAD30 | 6 | 138*150 | 14.5 | 28 | 217 | 3200*1400*1800 | 3400 |
| ZY-320GF | 320 400 | 576 | WD145TAD33L | 6 | 138*160 | 14.5 | 28 | 198 | 3500*1600*1900 | 3600 |
| ZY-350GF | 350 437.5 | 630 | WD145TAD35 | 6 | 138*160 | 14.5 | 28 | 198 | 3500*1600*1980 | 3700 |
| ZY-380GF | 380 475 | 684 | WD269TAD38 | 12 | 138*150 | 26.9 | 50 | 198 | 3600*1650*1900 | 3850 |
| ZY-400GF | 400 500 | 720 | WD269TAD41 | 12 | 135*150 | 26.9 | 50 | 198 | 3650*1650*1900 | 3900 |
| ZY-420GF | 420 525 | 756 | WD269TAD43 | 12 | 138*150 | 26.9 | 50 | 198 | 3650*1650*1900 | 3950 |
| ZY-450GF | 450 562.5 | 810 | WD269TAD45 | 12 | 138*150 | 26.9 | 50 | 198 | 3650*1650*1900 | 4000 |
| ZY-480GF | 480 600 | 864 | WD269TAD48 | 12 | 138*150 | 26.9 | 50 | 198 | 3650*1650*1900 | 4100 |
| ZY-500GF | 500 625 | 900 | WD269TAD50 | 12 | 138*150 | 26.9 | 50 | 213 | 3650*1650*1900 | 4100 |
| ZY-560GF | 560 700 | 1008 | WD269TAD56 | 12 | 138*150 | 26.9 | 50 | 213 | 3650*1650*1900 | 4200 |
| ZY-580GF | 580 725 | 1044 | WD287TAD58 | 12 | 138*160 | 28.7 | 50 | 221 | 3650*1650*1900 | 4200 |
| ZY-620GF | 620 775 | 1116 | WD287TAD61L | 12 | 138*160 | 28.7 | 50 | 198 | 3650*1670*2070 | 4200 |
| ZY-680GF | 680 850 | 1224 | WD327TAD68 | 12 | 145*165 | 32.7 | 90 | 197 | 4000*1700*2000 | 4400 |
| ZY-780GF | 780 975 | 1404 | WD327TAD78 | 12 | 145*165 | 32.7 | 90 | 197 | 4100*1700*2000 | 4500 |
| ZY-820GF | 820 1025 | 1476 | WD327TAD82 | 12 | 145*165 | 32.7 | 90 | 196 | 4100*1880*2350 | 4700 |
| ZY-880GF | 880 1100 | 1584 | WD327TAD88 | 12 | 145*165 | 32.7 | 90 | 196 | 4150*1900*2350 | 4800 |
| ZY-900GF | 900 1125 | 1620 | WD327TAD92 | 12 | 145*165 | 32.7 | 90 | 196 | 4200*2000*2350 | 5100 |
| ZY-1000GF | 1000 1250 | 1800 | WD327TAD100 | 12 | 145*165 | 32.7 | 90 | 196 | 4300*2000*2350 | 5200 |
| ZY-1100GF | 1100 1375 | 1980 | WD360TAD110 | 12 | 152*165 | 35.9 | 110 | 196 | 4300*2000*2350 | 7800 |
| ZY-1200GF | 1200 1500 | 2160 | WD360TAD120 | 12 | 152*165 | 35.9 | 110 | 196 | 4500*2000*2350 | 8000 |



**康明斯系列
柴油发电机组**
CUMMINS SERIES

品牌介绍 / Brand

康明斯系列柴油发电机组是采用中美合资B、N、K系列发动机为引擎，其可靠性、经济性一直以来赢得部队、工程、工矿企业的信赖。

康明斯公司创建于1919年2月，总部设在美国印第安纳州哥伦布市，康明斯在全球190多个国家和地区，500多家分销机构，服务网点遍布世界各地，为客户提供了可以信赖的服务保障。作为中国发动机行业最大的外国投资者，康明斯在中国拥有东风康明斯发动机有限公司（生产B、C、L系列）和重庆康明斯发动机有限公司（生产M、N、K系列）等制造企业。

Cummine series diesel gen-sets adopt the B,N,kseries engine(sino-us JVC),which is widely used in army、engineering,mining industry、more reliable、economic .Cummins company was founded in1919、the H.Q is in Columbus、indiana(USA),and have about 500 distributors spreading in 190 countries and regions,providing customers high efficient service, fast connection with the company.As the top one of JVC in China diesel gen-sets industry,Dongfeng Cummins Engine Co,Ltd(ForB,C,L series& Chongqing Cummins Engine Co Ltd(for M,N,K series)are its branches.

| 标准配置 | 可选配置 |
|--------------------|--------------------|
| Standard equipment | Optional equipment |

标准配置

- ◆发动机
- ◆启动免维护蓄电池及蓄电池连接线
- ◆40°C散热水箱
- ◆工业消声器、波纹
- ◆发电机
- ◆输出断路器
- ◆智能控制屏
- ◆钢式底架

可选配置

- ◆静音箱
- ◆全自动控制系统
- ◆50°C散热水箱
- ◆水套加热器
- ◆自动并机柜控制系统

Standard equipment

- ◆Diesel engine
- ◆Starting batteries and battery connect wires
- ◆40°Cwater cooled radiator
- ◆Silencer and flexible exhaust ho
- ◆Alternator
- ◆Output circuit breaker
- ◆Digital control panel
- ◆Steel base frame

Optional equipment

- ◆Sound proof
- ◆ATS
- ◆50°CWater cooled radiator
- ◆Water heater
- ◆Automatic parallel synchronizing contror system

规格参数 / Specifications

| 机组型号 (Model) | 功率Power KW KVA | 电流A Current | 发动机型号 Engine model | 缸数 Cyinder | 缸径*行程 Bore*Stoke | 排气量L Displacement | 机油容量L Lube oil | 油耗g/kwh Consumption | 尺寸mm SIZE | 重量Kg Weight |
|-----------------|-------------------|----------------|-----------------------|---------------|---------------------|----------------------|-------------------|------------------------|----------------|----------------|
| ZY-24GF | 24 30 | 43.2 | 4B3.9-G2 | 4 | 102*120 | 3.9 | 11 | 208 | 1620*710*1100 | 710 |
| ZY-30GF | 30 37.5 | 54 | 4BT3.9-G2 | 4 | 102*120 | 3.9 | 11 | 208 | 1700*710*1100 | 800 |
| ZY-40GF | 40 50 | 72 | 4BTA3.9-G2 | 4 | 102*120 | 3.9 | 11 | 210 | 1800*800*1200 | 920 |
| ZY-50GF | 50 62.5 | 90 | 4BTA3.9-G2 | 4 | 102*120 | 3.9 | 11 | 210 | 1800*800*1200 | 950 |
| ZY-64GF | 64 80 | 115.2 | 4BTA3.9-G11 | 4 | 102*120 | 3.9 | 11 | 210 | 1850*800*1200 | 1000 |
| ZY-80GF | 80 100 | 144 | 6BT5.9-G2 | 6 | 102*120 | 5.9 | 16 | 210 | 2200*800*1200 | 1250 |
| ZY-100GF | 100 125 | 180 | 6BTA5.9-G2 | 6 | 102*120 | 5.9 | 20 | 207 | 2200*800*1200 | 1300 |
| ZY-120GF | 120 150 | 216 | 6BTAA5.9-G2 | 6 | 102*120 | 5.9 | 24 | 207 | 2250*800*1200 | 1350 |
| ZY-132GF | 132 165 | 237.6 | 6BTAA5.9-G12 | 6 | 102*120 | 5.9 | 24 | 207 | 2300*8200*1300 | 1350 |
| ZY-150GF | 150 187.5 | 270 | 6CTA8.3-G2 | 6 | 114*135 | 8.3 | 24 | 207 | 2300*8200*1330 | 1600 |
| ZY-180GF | 180 225 | 324 | 6CTAAB.3-G2 | 6 | 114*135 | 8.3 | 24 | 207 | 2500*1050*1480 | 1700 |
| ZY-200GF | 200 250 | 360 | 6LTA8.9-G2 | 6 | 114*145 | 8.9 | 28 | 207 | 2500*1050*1500 | 2000 |
| ZY-220GF | 220 275 | 396 | 6LTA8.9-G3 | 6 | 114*145 | 8.9 | 28 | 203 | 2550*1050*1500 | 2000 |
| ZY-400GF | 400 500 | 720 | QSZ13-G2 | 6 | 130*163 | 13 | 28 | 201 | 3150*1360*1800 | 3200 |
| ZY-450GF | 450 562.5 | 810 | QSZ13-G3 | 6 | 130*163 | 13 | 28 | 201 | 3160*1360*1800 | 3300 |
| ZY-200GF | 200 250 | 360 | MTA11-G2 | 6 | 125*147 | 11 | 38 | 206 | 3000*1050*1700 | 2200 |
| ZY-200GF | 200 250 | 360 | NT855-GA | 6 | 140*150 | 14 | 28 | 206 | 3000*1050*1700 | 2600 |
| ZY-250GF | 250 312.5 | 450 | NTA855-G1A | 6 | 140*152 | 14 | 38 | 207 | 3100*1050*1700 | 2600 |
| ZY-280GF | 280 350 | 504 | MTA11-G3 | 6 | 125*147 | 11 | 38 | 210 | 3100*1050*1700 | 2700 |
| ZY-280GF | 280 350 | 504 | NTA855-G1B | 6 | 140*152 | 14 | 38 | 206 | 3100*1050*1700 | 2950 |
| ZY-300GF | 300 375 | 540 | NTA855-G2A | 6 | 140*152 | 14 | 38 | 206 | 3100*1100*1750 | 3000 |
| ZY-320GF | 320 400 | 576 | NTA855-G4 | 6 | 140*152 | 14 | 38 | 205 | 3100*1150*1800 | 3100 |
| ZY-320GF | 320 400 | 576 | QSNT-G3 | 6 | 140*152 | 14 | 38 | 205 | 3250*1200*1800 | 3100 |
| ZY-350GF | 350 437.5 | 630 | NTAA855-G7A | 6 | 140*152 | 14 | 38 | 205 | 3250*1200*1800 | 3500 |
| ZY-400GF | 400 500 | 720 | KTA19-G3A | 6 | 159*159 | 19 | 50 | 206 | 3500*1350*1800 | 3800 |
| ZY-500GF | 500 625 | 900 | KTA19-G8 | 6 | 159*159 | 19 | 50 | 206 | 3500*1380*1800 | 4000 |
| ZY-530GF | 530 662.5 | 954 | KTAA19-G6A | 6 | 159*159 | 19 | 50 | 206 | 3500*1560*2100 | 4200 |
| ZY-600GF | 600 750 | 1080 | KT38-GA | 12 | 159*159 | 38 | 100 | 206 | 4350*1800*2350 | 7000 |
| ZY-640GF | 640 800 | 1152 | KTA38-G2 | 12 | 159*159 | 38 | 100 | 206 | 4350*1800*2350 | 7500 |
| ZY-700GF | 700 875 | 1260 | KTA38-G2B | 12 | 159*159 | 38 | 100 | 206 | 4350*1800*2350 | 7500 |
| ZY-800GF | 800 1000 | 1440 | KTA38-G2A | 12 | 159*159 | 38 | 100 | 206 | 4350*1800*2350 | 7500 |
| ZY-824GF | 824 1030 | 1483 | KTA38-G5 | 12 | 159*159 | 38 | 120 | 208 | 4350*1800*2350 | 8000 |
| ZY-900GF | 900 1125 | 1620 | KTA38-G9 | 12 | 159*159 | 38 | 135 | 208 | 4450*1800*2350 | 8200 |
| ZY-1000GF | 1000 1250 | 1800 | KTA38-G9 | 12 | 159*159 | 38 | 135 | 208 | 4450*1850*2350 | 8200 |
| ZY-1100GF | 1100 1375 | 1980 | KTA50-G3 | 16 | 159*159 | 50 | 177 | 205 | 5000*2040*2430 | 9500 |
| ZY-1200GF | 1200 1500 | 2160 | KTA50-G8 | 16 | 159*159 | 50 | 204 | 205 | 5350*2110*2500 | 10000 |
| ZY-1200GF | 1200 1500 | 2160 | KTA50-GS8 | 16 | 159*159 | 50 | 204 | 205 | 5600*2150*2600 | 11000 |



潍柴动力系列 柴油发电机组

WEICHAI SERIES

品牌介绍 / Brand

潍柴发电机组功率范围10-1000KW,机组使用潍柴集团自主研发生产的发动机,配置知名品牌发电机及控制器。发电机产品系列包括扬柴系列、道依茨WP4/WP6系列、WP10系列、WP12系列、WP13系列、160系列、170系列、博杜安系列等,使用这些发电机与引进技术生产的国内外知名的品牌发电机等相配套,生产国内技术领先的发电机组。

Weichai power generator power range is from 10-1000kw,this gen-set uses diesel engine produced by weichai power engine,which is independent research and developed,and equipped with famous alternator and control panel.Engine series include yangchai, Deutz WP4/WP6, WP10, WP12, WP13, 160, 170, baudouin etc.Using these engines with world and domestic well-known brand alternator to produce the leading diesel gen-set in China.

| 标准配置 | 可选配置 | Standard equipment | Optional equipment |
|------|------|--------------------|--------------------|
|------|------|--------------------|--------------------|

| 标准配置 | Standard equipment |
|-----------------|--|
| 发动机 | Diesel engine |
| 启动免维护蓄电池及蓄电池连接线 | Starting batteries and battery connect wires |
| 40°C散热水箱 | 40°Cwater cooled radiator |
| 工业消声器、波纹 | Silencer and flexible exhaust ho |
| 发电机 | Alternator |
| 输出断路器 | Output circuit breaker |
| 智能控制屏 | Digital control panel |
| 钢式底架 | Steel base frame |

| 可选配置 | Optional equipment |
|-----------|---|
| 静音箱 | Sound proof |
| 全自动控制系统 | ATS |
| 50°C散热水箱 | 50°CWater cooled radiator |
| 水套加热器 | Water heater |
| 自动并机柜控制系统 | Automatic parallel synchronizing control system |

规格参数 / Specifications

| 机组型号 (Model) | 功率Power KW KVA | 电流A Current | 发动机型号 Engine model | 缸数 Cylinder | 缸径*行程 Bore*Stroke | 排气量L Displacement | 机油容量L Lube oil | 油耗g/kwh Consumption | 尺寸mm SIZE | 重量Kg Weight | |
|-----------------|----------------------|----------------|-----------------------|----------------|----------------------|----------------------|-------------------|------------------------|--------------|----------------|------|
| ZY-16GF | 16 | 20 | 28.8 | WP2.1D18E2 | 4 | 85*92 | 2.09 | 12 | 235 | 1500*630*1100 | 650 |
| ZY-20GF | 20 | 25 | 35 | WP2.5D22E2 | 4 | 90*100 | 2.54 | 12 | 235 | 1550*630*1150 | 660 |
| ZY-30GF | 30 | 37.5 | 54 | WP3.9D33E2 | 4 | 102*118 | 3.86 | 12 | 235 | 1650*650*1180 | 700 |
| ZY-34GF | 34 | 42.5 | 61.2 | WP4.3D38E2 | 4 | 105*125 | 4.33 | 12 | 235 | 1650*650*1180 | 800 |
| ZY-40GF | 40 | 50 | 72 | WP4.6D44E2 | 4 | 108*125 | 4.58 | 12 | 235 | 1770*650*1180 | 820 |
| ZY-48GF | 48 | 60 | 86.4 | WP4.1D50E2 | 4 | 105*118 | 4.09 | 12 | 215 | 1770*650*1180 | 820 |
| ZY-58GF | 58 | 72.5 | 104.4 | WP4.3D61E2 | 4 | 108*118 | 4.32 | 12 | 210 | 1800*650*1200 | 850 |
| ZY-30GF | 30 | 37.5 | 54 | D226B-3D | 3 | 105*120 | 3.12 | 7.25 | 215 | 1750*750*1350 | 610 |
| ZY-40GF | 40 | 50 | 72 | TD226B-3D | 3 | 105*120 | 3.12 | 7.25 | 215 | 1750*750*1350 | 620 |
| ZY-50GF | 50 | 62.5 | 90 | WP4D66E200 | 4 | 105*130 | 4.5 | 28 | 198 | 1950*800*1340 | 1000 |
| ZY-60GF | 60 | 75 | 108 | WP4D66E200 | 4 | 105*130 | 4.5 | 28 | 198 | 1950*800*1340 | 1000 |
| ZY-80GF | 80 | 100 | 144 | WP4D100E200 | 4 | 105*130 | 4.5 | 28 | 198 | 2200*800*1340 | 1100 |
| ZY-90GF | 90 | 112.5 | 162 | WP4D100E200 | 4 | 105*130 | 4.5 | 28 | 198 | 2200*800*1340 | 1100 |
| ZY-90GF | 90 | 112.5 | 162 | WP4D108E200 | 4 | 105*130 | 4.5 | 28 | 198 | 2200*820*1340 | 1250 |
| ZY-100GF | 100 | 125 | 180 | WP4D108E200 | 4 | 105*130 | 4.5 | 28 | 198 | 2200*820*1340 | 1250 |
| ZY-100GF | 100 | 125 | 180 | WP6D132E200 | 6 | 105*130 | 6.75 | 35 | 198 | 2300*830*1450 | 1250 |
| ZY-120GF | 120 | 150 | 216 | WP6D132E200 | 6 | 105*130 | 6.75 | 35 | 198 | 2470*930*1450 | 1550 |
| ZY-120GF | 120 | 150 | 216 | WP6D152E200 | 6 | 105*130 | 6.75 | 35 | 198 | 2470*930*1450 | 1620 |
| ZY-132GF | 132 | 165 | 237.6 | WP6D152E200 | 6 | 105*130 | 6.75 | 39 | 198 | 2470*930*1450 | 1620 |
| ZY-180GF | 150 | 187.5 | 270 | WP10D200E200 | 6 | 126*130 | 9.726 | 35 | 195 | 2750*1050*1800 | 1900 |
| ZY-200GF | 200 | 250 | 360 | WP10D238E200 | 6 | 126*130 | 9.726 | 35 | 195 | 2750*1050*1800 | 2100 |
| ZY-240GF | 220 | 275 | 396 | WP10D264E200 | 6 | 126*130 | 9.726 | 35 | 195 | 2900*1100*1800 | 2200 |
| ZY-280GF | 250 | 312.5 | 450 | WP12D317E200 | 6 | 126*155 | 11.596 | 38 | 195 | 2900*1100*1800 | 2300 |
| ZY-300GF | 300 | 375 | 540 | WP13D385E200 | 6 | 127*165 | 12.54 | 48 | 195 | 3000*1150*1800 | 2400 |
| ZY-350GF | 300 | 375 | 540 | WP13D385E200 | 6 | 127*165 | 12.54 | 48 | 195 | 3050*1150*1800 | 2500 |
| ZY-400GF | 400 | 500 | 720 | 6M26D447E200 | 6 | 150*150 | 15.9 | 65 | 210 | 3500*1500*1800 | 4000 |
| ZY-440GF | 440 | 550 | 792 | 6M26D484E200 | 6 | 150*150 | 15.9 | 65 | 210 | 3500*1500*1800 | 4800 |
| ZY-500GF | 500 | 625 | 900 | 6M33D572E200 | 6 | 150*185 | 19.6 | 65 | 210 | 3600*1500*1850 | 5000 |
| ZY-550GF | 550 | 687.5 | 990 | 6M33D605E200 | 6 | 150*185 | 19.6 | 65 | 210 | 3600*1500*1850 | 5000 |
| ZY-700GF | 700 | 875 | 1260 | 12M26D792E200 | 12 | 150*150 | 31.8 | 120 | 210 | 4500*1800*2200 | 7800 |
| ZY-800GF | 800 | 1000 | 1440 | 12M26D902E200 | 12 | 150*150 | 31.8 | 120 | 210 | 4500*1850*2200 | 8000 |
| ZY-880GF | 880 | 1100 | 1584 | 12M26D968E200 | 12 | 150*150 | 31.8 | 120 | 210 | 4600*1850*2250 | 8500 |
| ZY-1000GF | 1000 | 1250 | 1800 | 12M33D1108E200 | 12 | 150*185 | 39.2 | 146 | 210 | 4800*2000*2350 | 9200 |
| ZY-1100GF | 1100 | 1375 | 1980 | 12M33D1210E200 | 12 | 150*185 | 39.2 | 146 | 210 | 4800*2050*2450 | 9500 |



广西玉柴系列 柴油发电机组

YUCHAI SERIES

品牌介绍 / Brand

广西玉柴发动机是采用德国FEV技术所开发的产品。机体、气缸盖采用合金铸铁，强化程度高，采用整体锻钢曲轴，滑动轴承，体积小重量轻，可靠性高；大修期大于12000小时。该机组具有结构紧凑、功率储备大、可靠性高、调速性能好等特点。

Guangxi Yuchai diesel gen-sets is the series that produced by adopting the FEV technology from Germany. The machine body and cylinder are made of the high-strength alloy cast iron, fixed one-piece forged steel crankshaft, which have sliding bearing, fine, light weight and reliable quality. The yuchai diesel gen-sets have the great performance, compact structure, big power margin. normally the overhaul period must be after 12000 hours.

| 标准配置 | 可选配置 |
|--------------------|--------------------|
| Standard equipment | Optional equipment |

标准配置

发动机
启动免维护蓄电池及蓄电池连接线
40°C散热水箱
工业消声器、波纹
发电机
输出断路器
智能控制屏
钢式底架

Standard equipment

Diesel engine
Starting batteries and battery connect wires
40°C water cooled radiator
Silencer and flexible exhaust ho
Alternator
Output circuit breaker
Digital control panel
Steel base frame

可选配置

静音箱
全自动控制系统
50°C散热水箱
水套加热器
自动并机柜控制系统

Optional equipment

Sound proof
ATS
50°C Water cooled radiator
Water heater
Automatic parallel synchronizing control system

规格参数 / Specifications

| 机组型号 (Model) | 功率Power KW KVA | 电流A Current | 发动机型号 Engine model | 缸数 Cylinder | 缸径*行程 Bore*Stroke | 排气量L Displacement | 机油容量L Lube oil | 油耗g/kw.h Consumption | 尺寸mm SIZE | 重量Kg Weight | |
|-----------------|----------------------|----------------|-----------------------|----------------|----------------------|----------------------|-------------------|-------------------------|--------------|----------------|-------|
| ZY-24GF | 24 | 30 | 43.2 | YC2115D | 2 | 115*120 | 2.49 | 6.5 | 225 | 1500*750*1050 | 650 |
| ZY-30GF | 30 | 37.5 | 54 | YC2115ZD | 2 | 115*120 | 2.49 | 6.5 | 225 | 1500*800*1150 | 700 |
| ZY-40GF | 40 | 50 | 72 | YCD4J12D-55 | 4 | 105*125 | 4.33 | 11 | 225 | 1800*800*1100 | 800 |
| ZY-50GF | 50 | 62.5 | 90 | YCD4J22D-65 | 4 | 105*125 | 4.33 | 11 | 225 | 1800*800*1100 | 940 |
| ZY-50GF | 50 | 62.5 | 90 | YC4D85Z-D20 | 4 | 108*115 | 4.21 | 11 | 230 | 1920*800*1100 | 950 |
| ZY-60GF | 60 | 75 | 108 | YC4D90Z-D20 | 4 | 108*115 | 4.21 | 11 | 230 | 2000*800*1250 | 1100 |
| ZY-90GF | 90 | 112.5 | 162 | YC6B135Z-D20 | 6 | 108*125 | 6.87 | 20 | 197 | 2250*800*1300 | 1300 |
| ZY-100GF | 100 | 125 | 180 | YC6B155L-D21 | 6 | 108*125 | 6.87 | 20 | 196 | 2500*800*1300 | 1500 |
| ZY-120GF | 120 | 150 | 216 | YC6B180L-D20 | 6 | 108*125 | 6.87 | 20 | 196 | 2500*830*1300 | 1600 |
| ZY-132GF | 132 | 165 | 237.6 | YC6B205L-D20 | 6 | 108*125 | 6.87 | 20 | 196 | 2500*850*1300 | 1700 |
| ZY-150GF | 150 | 187.5 | 270 | YC6A230L-D20 | 6 | 108*132 | 7.26 | 21 | 195 | 2550*900*1350 | 2100 |
| ZY-160GF | 160 | 200 | 288 | YC6A245L-D21 | 6 | 108*132 | 7.26 | 21 | 195 | 2500*970*1500 | 2300 |
| ZY-180GF | 180 | 225 | 324 | YC6MK285L-D20 | 6 | 123*145 | 10.33 | 28 | 195 | 3000*1030*1550 | 2600 |
| ZY-200GF | 200 | 250 | 360 | YC6MK350L-D20 | 6 | 123*145 | 10.33 | 28 | 195 | 3000*1030*1580 | 2750 |
| ZY-220GF | 220 | 275 | 396 | YC6MK350L-D20 | 6 | 123*145 | 10.33 | 28 | 195 | 3100*1100*1750 | 2800 |
| ZY-250GF | 250 | 312.5 | 450 | YC6MK420L-D20 | 6 | 123*145 | 10.33 | 28 | 195 | 3100*1150*1750 | 3000 |
| ZY-280GF | 280 | 350 | 504 | YC6MK420L-D20 | 6 | 123*145 | 10.33 | 28 | 195 | 3100*1150*1700 | 3000 |
| ZY-300GF | 300 | 375 | 540 | YC6MJ480L-D20 | 6 | 131*145 | 11.73 | 28 | 215 | 3100*1150*1750 | 3100 |
| ZY-320GF | 320 | 400 | 576 | YC6MJ480L-D20 | 6 | 131*145 | 11.73 | 28 | 215 | 3200*1200*175 | 3100 |
| ZY-350GF | 350 | 437.5 | 630 | YC6K520-D30 | 6 | 129*155 | 12.15 | 32 | 205 | 3300*1250*1850 | 3500 |
| ZY-380GF | 380 | 475 | 684 | YC6K570-D30 | 6 | 129*165 | 12.94 | 32 | 205 | 3400*1250*1850 | 3600 |
| ZY-400GF | 400 | 500 | 720 | YC6T600L-D22 | 6 | 145*165 | 16.35 | 52 | 195 | 3500*1350*1780 | 3900 |
| ZY-440GF | 440 | 550 | 792 | YC6T660L-D20 | 6 | 145*165 | 16.35 | 52 | 195 | 3500*1500*1970 | 4000 |
| ZY-500GF | 500 | 625 | 900 | YC6TD780L-D20 | 6 | 152*180 | 19.6 | 52 | 225 | 3580*1500*1830 | 4100 |
| ZY-550GF | 550 | 687.5 | 990 | YC6TD840L-D20 | 6 | 152*180 | 19.6 | 52 | 225 | 3650*1600*2000 | 4200 |
| ZY-600GF | 600 | 750 | 1080 | YC6TD900-D31 | 6 | 152*180 | 19.6 | 52 | 225 | 3750*1650*2000 | 4500 |
| ZY-650GF | 650 | 812.5 | 1170 | YC6TD1000-D30 | 6 | 150*180 | 19.6 | 52 | 225 | 3750*1650*2000 | 4500 |
| ZY-650GF | 650 | 812.5 | 1170 | YC6C1020-D31 | 6 | 200*210 | 39.58 | 180 | 220 | 4000*1650*2100 | 5500 |
| ZY-700GF | 700 | 875 | 1260 | YC6C1070-D31 | 6 | 200*210 | 39.58 | 180 | 220 | 4200*1650*2100 | 5800 |
| ZY-800GF | 800 | 1000 | 1440 | YC6C1220-D31 | 6 | 200*210 | 39.58 | 180 | 220 | 4600*1800*2600 | 8000 |
| ZY-880GF | 880 | 1000 | 1584 | YC6C1320-D31 | 6 | 200*210 | 39.58 | 180 | 220 | 5200*2150*2600 | 8500 |
| ZY-1000GF | 1000 | 1250 | 1800 | YC6C1520-D31 | 6 | 200*210 | 39.58 | 180 | 220 | 5200*2150*2600 | 9800 |
| ZY-1100GF | 1100 | 1375 | 1980 | YC12VC1680-D31 | 12 | 200*210 | 79.17 | 280 | 210 | 5400*2150*2600 | 9900 |
| ZY-1200GF | 1200 | 1500 | 2160 | YC12VC2070-D31 | 12 | 200*210 | 79.17 | 280 | 210 | 5400*2300*2600 | 9000 |
| ZY-1320GF | 1320 | 1650 | 2376 | YC12VC2070-D31 | 12 | 200*210 | 79.17 | 280 | 210 | 5400*2300*2600 | 10000 |
| ZY-1500GF | 1500 | 1875 | 2700 | YC12VC2270-D31 | 12 | 200*210 | 79.17 | 280 | 210 | 5600*2300*2600 | 12000 |
| ZY-1600GF | 1600 | 2000 | 2880 | YC12VC2510-D31 | 12 | 200*210 | 79.17 | 280 | 210 | 5600*2300*2600 | 12500 |
| ZY-1800GF | 1800 | 2250 | 3240 | YC12VC2700-D31 | 12 | 200*210 | 79.17 | 280 | 210 | 5650*2350*2600 | 13200 |
| ZY-2000GF | 2000 | 5000 | 3600 | YC16VC3000-D31 | 16 | 200*210 | 105.6 | 430 | 196 | 7350*2670*2950 | 17500 |
| ZY-2200GF | 2200 | 2750 | 3960 | YC16VC3300-D31 | 16 | 200*210 | 105.6 | 430 | 196 | 7350*2670*2950 | 17580 |
| ZY-2400GF | 2400 | 3000 | 4320 | YC16VC3600-D31 | 16 | 200*210 | 105.6 | 430 | 196 | 7400*3100*3300 | 19200 |



上柴系列 柴油发电机组

SDEC SERIES

品牌介绍 / Brand

该系列发电机组采用上海柴油机股份有限公司生产H系列、D系列、E系列、G系列、W系列电站柴油机作为动力，配置名牌发电机。机组具有调压精度高、动态性能好、电压波形畸变小、效率高、工作可靠、使用寿命长、经济性能好等特点。机组配置全套免维护蓄电池启动系统，用户只需注入机油和冷冻液、接通负极开关后即可启动机组，输出电力，极大提高了使用的便捷性。

SDEC series diesel generator set adopt the H,D,E,G, W series diesel engine, which are made by Shanghai Diesel Engine Co., Ltd, and the famous alternators. The genset has the characteristics of high precision, high dynamic performance, low voltage waveform distortion, high efficiency, reliable operation, long service life and good economic performance. The genset is equipped with a maintenance-free battery start system. User only need to inject oil and coolant. After turning on the negative switch, the user can start the unit and output the power, which greatly improves the convenience of the use.

| 标准配置 | 可选配置 |
|--------------------|--------------------|
| Standard equipment | Optional equipment |

标准配置

发动机
启动免维护蓄电池及蓄电池连接线
40°C散热器水箱
工业消声器、波纹
发电机
输出断路器
智能控制屏
钢式底架

Standard equipment

Diesel engine
Starting batteries and battery connect wires
40°C water cooled radiator
Silencer and flexible exhaust ho
Alternator
Output circuit breaker
Digital control panel
Steel base frame

可选配置


静音箱
全自动控制系统
50°C散热器水箱
水套加热器
自动并机柜控制系统

Optional equipment

Sound proof
ATS
50°C Water cooled radiator
Water heater
Automatic parallel synchronizing control system

规格参数 / Specifications

| 机组型号 (Model) | 功率Power KW KVA | 电流A Current | 发动机型号 Engine model | 缸数 Cylinder | 缸径*行程 Bore*Stroke | 排气量L Displacement | 机油容量L Lube oil | 油耗g/kw.h Consumption | 尺寸mm SIZE | 重量Kg Weight | |
|-----------------|----------------------|----------------|-----------------------|----------------|----------------------|----------------------|-------------------|-------------------------|--------------|----------------|------|
| ZY-50GF | 50 | 62.5 | 90 | SC4H95D2 | 4 | 105*124 | 4.3 | 13 | 195 | 1900*800*1200 | 950 |
| ZY-75GF | 75 | 93.75 | 135 | SC4H115D2 | 4 | 105*124 | 4.3 | 13 | 195 | 1900*800*1200 | 1000 |
| ZY-100GF | 100 | 125 | 180 | SC4H160D2 | 4 | 105*124 | 4.3 | 13 | 195 | 2060*900*1200 | 1100 |
| ZY-120GF | 120 | 150 | 216 | SC4H180D2 | 4 | 105*124 | 4.3 | 13 | 195 | 2100*900*1200 | 1350 |
| ZY-150GF | 150 | 187.5 | 270 | SC7H230D2 | 6 | 105*124 | 6.5 | 17.5 | 195 | 2400*950*1450 | 1700 |
| ZY-170GF | 170 | 212.5 | 306 | SC7H250D2 | 6 | 105*124 | 6.5 | 17.5 | 195 | 2600*950*1500 | 1800 |
| ZY-180GF | 180 | 225 | 324 | SC8D280D2 | 6 | 114*135 | 8.3 | 19 | 200 | 2600*1050*1500 | 1800 |
| ZY-200GF | 200 | 250 | 360 | SC9D310D2 | 6 | 114*144 | 8.9 | 19 | 200 | 2600*1050*1500 | 1850 |
| ZY-220GF | 220 | 275 | 396 | SC9D340D2 | 6 | 114*144 | 8.9 | 25 | 198 | 3000*1150*1650 | 2500 |
| ZY-250GF | 250 | 312.5 | 450 | SC13G355D2 | 6 | 135*150 | 12.88 | 41 | 205 | 3000*1150*1650 | 2550 |
| ZY-280GF | 250 | 312.5 | 450 | SC13G420D2 | 6 | 135*150 | 12.88 | 41 | 225 | 3000*1150*1650 | 2550 |
| ZY-300GF | 300 | 375 | 540 | SC12E460D2 | 6 | 128*153 | 11.8 | 41 | 192 | 3100*1150*1650 | 2650 |
| ZY-320GF | 320 | 400 | 576 | SC15G500D2 | 6 | 135*165 | 14.2 | 41 | 205 | 3100*1250*1650 | 2700 |
| ZY-350GF | 350 | 437.5 | 630 | SC15G500D2 | 6 | 135*165 | 14.2 | 41 | 205 | 3150*1250*1650 | 2800 |
| ZY-400GF | 400 | 500 | 720 | SC25G610D2 | 12 | 135*150 | 25.8 | 65 | 205 | 3500*1500*1950 | 3900 |
| ZY-450GF | 450 | 562.5 | 810 | SC25G690D2 | 12 | 135*150 | 25.8 | 65 | 205 | 3500*1500*1950 | 4000 |
| ZY-500GF | 500 | 625 | 900 | SC27G755D2 | 12 | 135*155 | 26.6 | 65 | 205 | 3500*1500*2000 | 4200 |
| ZY-550GF | 550 | 687.5 | 990 | SC27G830D2 | 12 | 135*155 | 26.6 | 65 | 205 | 3650*1500*2000 | 4300 |
| ZY-600GF | 600 | 750 | 1080 | SC27G900D2 | 12 | 135*155 | 26.6 | 65 | 205 | 3700*1500*2150 | 4400 |
| ZY-660GF | 660 | 825 | 1188 | SC33W990D2 | 6 | 180*215 | 32.8 | 75 | 205 | 4400*1700*2150 | 6500 |
| ZY-800GF | 800 | 1000 | 1440 | SC33W1150D2 | 6 | 180*215 | 32.8 | 75 | 205 | 4500*1800*2350 | 6500 |





上海乾能系列 柴油发电机组

SHANGHAI QIANNENG SERIES

品牌介绍 / Brand

上海乾能系列发电机组是我公司采用上海乾能内燃机有限公司生产的发电机配置名牌发电机而成，功率从120KW-1000KW。为用户提供广泛的选择。上海乾能柴油发电机组运行成本低，售后服务周到，备受用户青睐。

Shanghai Qian Neng diesel generator power is from 120KW/150kva to 1000kw/1250kva. With low cost operation, timely and excellent after sales service of Shanghai Qian Neng diesel generators, more and more customer would like to choose it.

| 标准配置 | 可选配置 |
|--------------------|--------------------|
| Standard equipment | Optional equipment |

标准配置

发动机
启动免维护蓄电池及蓄电池连接线
40°C散热水箱
工业消声器、波纹
发电机
输出断路器
智能控制屏
钢式底架

Standard equipment

Diesel engine
Starting batteries and battery connect wires
40°C water cooled radiator
Silencer and flexible exhaust hose
Alternator
Output circuit breaker
Digital control panel
Steel base frame

可选配置

静音箱
全自动控制系统
50°C散热水箱
水套加热器
自动并机柜控制系统

Optional equipment

Sound proof
ATS
50°C Water cooled radiator
Water heater
Automatic parallel synchronizing control system

规格参数 / Specifications

| 机组型号 (Model) | 功率Power KW KVA | 电流A Current | 发动机型号 Engine model | 缸数 Cylinder | 缸径*行程 Bore*Stroke | 排气量L Displacement | 机油容量L Lube oil | 油耗g/kw.h Consumption | 尺寸mm SIZE | 重量Kg Weight | |
|-----------------|-------------------|----------------|-----------------------|----------------|----------------------|----------------------|-------------------|-------------------------|--------------|----------------|------|
| ZY-150GF | 150 | 187.5 | 270 | QN8H163 | 6 | 114*135 | 8.27 | 28 | 198 | 2700*950*1650 | 1550 |
| ZY-150GF | 150 | 187.5 | 270 | 6135AZD | 6 | 135*150 | 12.9 | 28 | 226 | 2700*950*1650 | 1580 |
| ZY-180GF | 180 | 225 | 324 | QN8H217 | 6 | 114*144 | 8.27 | 28 | 198 | 2800*950*1650 | 1590 |
| ZY-180GF | 180 | 225 | 324 | 6135BZD | 6 | 135*150 | 12.9 | 28 | 226 | 2800*950*1650 | 1610 |
| ZY-200GF | 200 | 250 | 360 | QN9H245 | 6 | 114*144 | 8.27 | 28 | 198 | 2800*1150*1700 | 1650 |
| ZY-200GF | 200 | 250 | 360 | 6135AZLD | 6 | 135*150 | 12.9 | 28 | 226 | 2900*1150*1700 | 1720 |
| ZY-220GF | 220 | 275 | 396 | QN13H340 | 6 | 135*150 | 12.9 | 34 | 200 | 3100*1150*1800 | 2300 |
| ZY-220GF | 220 | 275 | 396 | 6135BZLD | 6 | 135*150 | 25.8 | 34 | 207 | 3100*1150*1800 | 2330 |
| ZY-250GF | 250 | 312.5 | 450 | QN13H340 | 6 | 135*150 | 12.9 | 34 | 200 | 3100*1150*1800 | 2600 |
| ZY-280GF | 280 | 350 | 504 | QN13H340 | 6 | 135*150 | 12.9 | 34 | 200 | 3150*1350*1800 | 2600 |
| ZY-280GF | 280 | 350 | 504 | 6135BZLD-3 | 6 | 135*150 | 12.9 | 34 | 207 | 3150*1350*1800 | 2600 |
| ZY-300GF | 300 | 375 | 540 | QN13H380 | 6 | 135*160 | 12.9 | 34 | 200 | 3150*1350*1800 | 2600 |
| ZY-320GF | 320 | 400 | 576 | QN13H435 | 6 | 135*160 | 12.9 | 34 | 200 | 3150*1350*1800 | 2600 |
| ZY-320GF | 320 | 400 | 576 | 6135CZLD | 6 | 135*155 | 12.9 | 34 | 193 | 3150*1350*1800 | 2600 |
| ZY-350GF | 350 | 437.5 | 630 | QN13H435 | 6 | 135*160 | 12.9 | 34 | 200 | 3200*1350*1900 | 2800 |
| ZY-350GF | 350 | 437.5 | 630 | 12V135AZLD | 12 | 135*150 | 25.8 | 57.4 | 225 | 3500*1350*1950 | 3550 |
| ZY-400GF | 400 | 500 | 720 | QN13H516 | 6 | 135*165 | 12.9 | 34 | 200 | 3200*1250*1750 | 3300 |
| ZY-400GF | 400 | 500 | 720 | 12V135AZLD-1 | 12 | 135*150 | 25.8 | 57.4 | 225 | 3500*1550*1950 | 3700 |
| ZY-450GF | 450 | 562.5 | 810 | QN26H571 | 12 | 135*150 | 26 | 57.4 | 210 | 3500*1700*1950 | 3800 |
| ZY-450GF | 450 | 562.5 | 810 | 12V135BZLD | 12 | 135*150 | 26.8 | 57.4 | 225 | 3500*1700*1950 | 3800 |
| ZY-500GF | 500 | 625 | 900 | QN26H612 | 12 | 135*155 | 26 | 57.4 | 205 | 3550*1700*1950 | 3850 |
| ZY-500GF | 500 | 625 | 900 | 12V135BZLD-1 | 12 | 135*150 | 26.8 | 57.4 | 225 | 3550*1700*1950 | 3850 |
| ZY-550GF | 550 | 687.5 | 990 | QN26H680 | 12 | 135*155 | 26 | 57.4 | 205 | 3550*1700*1950 | 3900 |
| ZY-550GF | 550 | 687.5 | 990 | 12V135BZLD-3 | 12 | 135*150 | 26.8 | 57.4 | 225 | 3550*1700*1950 | 4000 |
| ZY-600GF | 600 | 750 | 1080 | QN28H748 | 12 | 135*158 | 26 | 57.4 | 202 | 3600*1750*1950 | 4200 |
| ZY-600GF | 600 | 750 | 1080 | 12V138BZLD | 12 | 135*150 | 26.8 | 57.4 | 207 | 3600*1750*1950 | 4200 |
| ZY-600GF | 600 | 750 | 1080 | QN28H816 | 12 | 138*158 | 28 | 57.4 | 202 | 3600*1750*1950 | 4300 |
| ZY-640GF | 640 | 800 | 1152 | QN28H843 | 12 | 138*158 | 28 | 57.4 | 202 | 3600*1900*1950 | 4500 |
| ZY-700GF | 700 | 875 | 1260 | QN28H884 | 12 | 138*158 | 28 | 57.4 | 202 | 3600*1900*1950 | 4500 |
| ZY-700GF | 700 | 875 | 1260 | QN28H960 | 12 | 138*165 | 28 | 57.4 | 198 | 3600*1900*2000 | 4600 |
| ZY-800GF | 800 | 1000 | 1440 | QN28H1100 | 12 | 138*165 | 28 | 57.4 | 198 | 3850*1940*2250 | 4800 |
| ZY-880GF | 880 | 1100 | 1584 | QN28H1150 | 12 | 138*165 | 28 | 57.4 | 198 | 4300*1940*2300 | 5400 |
| ZY-900GF | 900 | 1125 | 1620 | QN32H1280 | 12 | 138*168 | 32 | 57.4 | 196 | 4300*1940*2300 | 5500 |
| ZY-1000GF | 1000 | 1250 | 1800 | QN32H1340 | 12 | 138*168 | 32 | 57.4 | 196 | 4500*1950*2300 | 5600 |



**VOLVO
PENTA**

**沃尔沃系列
柴油发电机组**

VOLVO SERIES

品牌介绍 / Brand

沃尔沃(Volvo)柴油发电机组属于环保型机组,排放标准达到欧盟二号或三号及EPA环保标准,发动机选用久负盛名的瑞典沃尔沃集团生产的电子喷射柴油发动机。沃尔沃公司始创于1927年,长期以来,他闪亮的品牌一直与它的三个核心价值观—质量、安全、环保紧密相联系在一起。沃尔沃(Volvo)柴油发电机组特点:冷启动特性好、加载能力强、体积小、耗油低、寿命长。

Volvo series diesel generator set are environmentally friendly,and the emission situation achieve European Union 2 or 3 and EPA environmental standards,which selects electronic injection diesel engines prestigious from Sweden Volvo group production.Volvo company is founded in1927,that shining brand is closely associated with its three core values-quality,safety,environmental protection. Volvo diesel generator set features:cold starting,strong loading capability,small volume,low fuel consumption,long service lite.

| | | | |
|-------------|-------------|--------------------|--------------------|
| 标准配置 | 可选配置 | Standard equipment | Optional equipment |
|-------------|-------------|--------------------|--------------------|

标准配置

- 发动机
- 发电机
- 启动免维护蓄电池及蓄电池连接线
- 输出断路器
- 40°C散热水箱
- 智能控制屏
- 工业消音器、波纹管
- 钢式底架

可选配置

- 静音箱
- 全自动控制系统
- 50°C散热水箱
- 水套加热器
- 自动并机控制系统

Standard equipment

- Diesel engine
- Alternator
- Starting batteries and battery connect wires
- Outout circuit breaker
- 40°C water cooled radiator
- Digital control panel
- Silencer and flexible exhaust hose
- Steel base frame

Optional equipment

- Sound proof
- ATS
- 50°C water cooled radiator
- Water heater
- Automatic parallel synchronizing control system

规格参数 / Specifications

| 机组型号 (Model) | 功率Power KW KVA | 电流A Current | 发动机型号 Engine model | 缸数 Cyinder | 缸径*行程 Bore*Stoke | 排气量L Displacement | 机油容量L Lube oil | 油耗g/kw.h Consumption | 尺寸mm SIZE | 重量Kg Weight | |
|-----------------|-------------------|----------------|-----------------------|---------------|---------------------|----------------------|-------------------|-------------------------|--------------|----------------|------|
| ZY-80GF | 80 | 100 | 144 | TAD530GE | 4 | 108*130 | 4.76 | 13 | 213 | 2100*700*1450 | 1030 |
| ZY-90GF | 90 | 112.5 | 162 | TAD531GE | 4 | 108*130 | 4.76 | 13 | 214 | 2100*800*1450 | 1150 |
| ZY-112GF | 112 | 140 | 201.6 | TAD532GE | 4 | 108*130 | 4.76 | 15 | 214 | 2200*900*1500 | 1200 |
| ZY-128GF | 128 | 160 | 230.4 | TAD731GE | 6 | 108*130 | 7.15 | 20 | 215 | 2500*1020*1550 | 1500 |
| ZY-160GF | 160 | 200 | 288 | TAD732GE | 6 | 108*130 | 7.15 | 34 | 213 | 2520*1060*1530 | 1700 |
| ZY-180GF | 180 | 225 | 324 | TAD733GE | 6 | 108*130 | 7.15 | 34 | 216 | 2550*1060*1530 | 1800 |
| ZY-200GF | 200 | 250 | 360 | TAD734GE | 6 | 108*130 | 7.15 | 29 | 204 | 2600*1100*1530 | 1950 |
| ZY-220GF | 220 | 275 | 396 | TAD734GE | 6 | 108*130 | 7.15 | 29 | 204 | 2600*1100*1530 | 1950 |
| ZY-280GF | 280 | 350 | 504 | TAD1341GE | 6 | 131*158 | 12.78 | 35 | 198 | 3100*1150*1600 | 2550 |
| ZY-300GF | 300 | 375 | 540 | TAD1342GE | 6 | 131*158 | 12.78 | 35 | 198 | 3100*1150*1600 | 2850 |
| ZY-320GF | 320 | 400 | 576 | TAD1343GE | 6 | 131*158 | 12.78 | 35 | 198 | 3100*1150*1600 | 2950 |
| ZY-350GF | 350 | 473.5 | 630 | TAD1344GE | 6 | 131*158 | 12.78 | 35 | 199 | 3100*1150*1600 | 3050 |
| ZY-400GF | 400 | 500 | 720 | TAD1345GE | 6 | 131*158 | 12.78 | 35 | 200 | 3200*1150*1800 | 3400 |
| ZY-440GF | 440 | 550 | 792 | TAD1641GE | 6 | 144*165 | 16.12 | 48 | 199 | 3300*1400*1950 | 3400 |
| ZY-480GF | 480 | 600 | 864 | TAD1642GE | 6 | 144*165 | 16.12 | 48 | 201 | 3300*1400*1950 | 3500 |
| ZY-500GF | 500 | 625 | 900 | TWD1643GE | 6 | 144*165 | 16.12 | 48 | 199 | 3350*1400*1950 | 3600 |
| ZY-550GF | 550 | 687.5 | 990 | TWD1643GE | 6 | 144*165 | 16.12 | 48 | 199 | 3400*1400*2000 | 3800 |





MTU系列 柴油发电机组

MTU SERIES

品牌介绍 / Brand

发动机及涡轮机联盟弗里德希哈芬股份有限公司，简称：MTU公司。MTU为戴姆勒-奔驰集团属下公司，是世界领先的柴油发动机制造商。其领先的技术、高可靠性的产品以及一流的售后服务，在世界范围内享有盛誉。其柴油发动机功率从35kw-9000kw,广泛用于舰船、重型汽车和工程机械、铁路机车。

Motoren-und Turbinen-Union Friedrichshafen GmbH,MTU,is one of the Daimler -Benz Group companies,and the world' s leading manufacturers of diesel engine.It has good reputation all over the world with its leading-edge technology,high quality products and excellent after-sales service.The power range of diesel engine is from 35kw to 9500kw.MTU series diesel gensets are widely used in the naval ships,heavy duty truck,construction machinery and railway locomotive

| 标准配置 | 可选配置 | Standard equipment | Optional equipment |
|------|------|--------------------|--------------------|
|------|------|--------------------|--------------------|

标准配置

发动机
启动免维护蓄电池及蓄电池连接线
40°C散热水箱
工业消声器、波纹
发电机
输出断路器
智能控制屏
钢式底架

Standard equipment

Diesel engine
Starting batteries and battery connect wires
40°Cwater cooled radiator
Silencer and flexible exhaust ho
Alternator
Output circuit breaker
Digital control panel
Steel base frame

可选配置

静音箱
全自动控制系统
50°C散热水箱
水套加热器
自动并机柜控制系统

Optional equipment

Sound proof
ATS
50°CWater cooled radiator
Water heater
Automatic parallel synchronizing control system

规格参数 / Specifications

| 机组型号 (Model) | 功率Power KW KVA | 电流A Current | 发动机型号 Engine model | 缸数 Cyinder | 缸径*行程 Bore*Stroke | 排气量L Displacement | 机油容量L Lube oil | 油耗g/kwh Consumption | 尺寸mm SIZE | 重量Kg Weight | |
|------------------|----------------------|----------------|-----------------------|---------------|----------------------|----------------------|-------------------|------------------------|--------------|----------------|-------|
| ZY-220GF | 220 | 275 | 396 | 6R1600G10F | 6 | 122*150 | 10.5 | 43 | 201 | 2800*1150*1650 | 2500 |
| ZY-250GF | 250 | 312.5 | 450 | 6R1600G20F | 6 | 122*150 | 10.5 | 46 | 199 | 2800*1150*1650 | 2900 |
| ZY-300GF | 300 | 375 | 540 | 8V1600G10F | 8 | 122*150 | 14 | 46 | 191 | 2840*1660*1975 | 3250 |
| ZY-320GF | 320 | 400 | 576 | 8V1600G20F | 8 | 122*150 | 14 | 46 | 190 | 2840*1660*1975 | 3250 |
| ZY-360GF | 360 | 450 | 648 | 10V1600G10F | 10 | 122*150 | 17.5 | 61 | 191 | 3230*1660*2040 | 3800 |
| ZY-400GF | 400 | 500 | 720 | 10V1600G20F | 10 | 122*150 | 17.5 | 61 | 190 | 3320*1350*1850 | 4000 |
| ZY-480GF | 480 | 600 | 864 | 12V1600G10F | 12 | 122*150 | 21 | 73 | 195 | 3300*1400*1970 | 3900 |
| ZY-500GF | 500 | 625 | 900 | 12V1600G20F | 12 | 122*150 | 21 | 73 | 195 | 3400*1350*1850 | 4410 |
| ZY-550GF | 550 | 687.5 | 990 | 12V2000G25 | 12 | 130*150 | 23.88 | 77 | 197 | 4000*1650*2280 | 6500 |
| ZY-630GF | 630 | 787.5 | 1134 | 12V2000G65 | 12 | 130*150 | 23.88 | 77 | 202 | 4200*1650*2280 | 7000 |
| ZY-800GF | 800 | 1000 | 1440 | 16V2000G25 | 16 | 130*150 | 31.84 | 102 | 198 | 4500*2000*2300 | 7800 |
| ZY-880GF | 880 | 1000 | 1584 | 16V2000G65 | 16 | 130*150 | 31.84 | 102 | 198 | 4500*2000*2300 | 7800 |
| ZY-1000GF | 1000 | 1250 | 1800 | 18V2000G65 | 18 | 130*150 | 35.82 | 130 | 202 | 4700*2000*2380 | 9000 |
| ZY-1100GF | 1100 | 1375 | 1980 | 18V2000G26F | 18 | 130*150 | 35.82 | 130 | 202 | 4700*2000*2380 | 9000 |
| ZY-1200GF | 1200 | 1500 | 2160 | 12V4000G23R | 12 | 170*210 | 57.2 | 260 | 195 | 5500*2220*2660 | 12000 |
| ZY-1400GF | 1400 | 1750 | 2520 | 12V4000G23 | 12 | 170*210 | 57.2 | 260 | 189 | 5500*2220*2660 | 12500 |
| ZY-1500GF | 1500 | 1875 | 2700 | 12V4000G63 | 12 | 170*210 | 57.2 | 260 | 193 | 5500*2220*2660 | 13000 |
| ZY-1760GF | 1760 | 2200 | 3168 | 16V4000G23 | 16 | 170*210 | 76.3 | 300 | 192 | 6500*2600*2660 | 17000 |
| ZY-1900GF | 1900 | 2375 | 3420 | 16V4000G63 | 16 | 170*210 | 76.3 | 300 | 191 | 6550*2600*2660 | 17500 |
| ZY-2200GF | 220 | 2750 | 3960 | 20V4000G23 | 20 | 170*210 | 95.4 | 390 | 195 | 8300*2950*2700 | 20500 |
| ZY-2400GF | 2400 | 3000 | 4320 | 20V4000G63 | 20 | 170*210 | 95.4 | 390 | 193 | 8300*2950*2700 | 21000 |
| ZY-2500GF | 2500 | 3125 | 4500 | 20V4000G63L | 20 | 170*210 | 95.4 | 390 | 192 | 8300*2950*2700 | 21000 |





帕金斯系列 柴油发电机组

PERKINS SERIES

品牌介绍 / Brand

英国帕金斯(又称劳斯莱斯)发动机有限公司是世界最大的发动机制造商之一,创立于1932年,年产量近40万台发动机。1998年,帕金斯被美国克莱斯勒公司控股,成为卡特集团一成员。帕金斯以飞快的速度为广大客户所接受,并迅速占领一部分市场份额,在发电机组市场上取得了令人瞩目的成就。帕金斯柴油发电机组规格全,品种多、结构紧凑、性能稳定可靠、一般维护保养易行、废气排放污染低达到欧三环保排放标准。

British perkins (also called Rolls-Royce engine Co. Ltd is one of the world's largest engine manufacturer,was founded in 1932, the annual output nearly 400,000 engines. In 1998, perkins was the US Chrysler holdings,becoming a member of Caterpillar Inc. Perkins engine gained remarkable achievement in generator market.Perkins diesel generator set have complete pecification, compact structure,reliable performance,easy general maintenance and exhaust emission meet European Union three environmental emissions standards.

| 标准配置 | 可选配置 |
|--------------------|--------------------|
| Standard equipment | Optional equipment |

标准配置

- 发动机
- 发电机
- 启动免维护蓄电池及蓄电池连接线
- 输出断路器
- 40°C散热水箱
- 智能控制屏
- 工业消音器、波纹管
- 钢式底架

可选配置

- 静音箱
- 全自动控制系统
- 50°C散热水箱
- 水套加热器
- 自动并机控制系统

Standard equipment

- Diesel engine
- Alternator
- Starting batteries and battery connect wires
- Outout circuit breaker
- 40°C water cooled radiator
- Digital control panel
- Silencer and flexible exhaust hose
- Steel base frame

Optional equipment

- Sound proof
- ATS
- 50°CWater cooled radiator
- Water heater
- Automatic parallel synchronizing control system

规格参数 / Specifications

| 机组型号 (Model) | 功率Power KW KVA | 电流A Current | 发动机型号 Engine model | 缸数 Cyinder | 缸径*行程 Bore*Stoke | 排气量L Displacement | 机油容量L Lube oil | 油耗g/kw.h Consumption | 尺寸mm SIZE | 重量Kg Weight | |
|-----------------|----------------------|----------------|-----------------------|----------------|---------------------|----------------------|-------------------|-------------------------|--------------|----------------|-------|
| ZY-7GF | 7 | 8.75 | 12.6 | 403A-11G1 | 3 | 77*81 | 1.13 | 4.9 | 248 | 1200*700*1100 | 300 |
| ZY-8GF | 8 | 10 | 14.4 | 403D-11G | 3 | 77*81 | 1.13 | 4.9 | 252 | 1200*700*1100 | 300 |
| ZY-10GF | 10 | 12.5 | 18 | 403D-15G | 3 | 84*90 | 1.49 | 6 | 248 | 1250*700*1100 | 350 |
| ZY-11GF | 11 | 13.75 | 19.8 | 403A-15G1 | 3 | 84*90 | 1.49 | 6.5 | 248 | 1250*700*1100 | 350 |
| ZY-12GF | 12 | 15 | 21.6 | 403A-15G2 | 3 | 84*90 | 1.49 | 6 | 250 | 1250*700*1100 | 350 |
| ZY-16GF | 16 | 20 | 28.8 | 404A-22G1 | 4 | 84*100 | 2.2 | 10.6 | 237 | 1500*710*1100 | 500 |
| ZY-16GF | 16 | 20 | 28.8 | 404D-22G | 4 | 84*100 | 2.2 | 10.6 | 237 | 1500*710*1100 | 500 |
| ZY-24GF | 24 | 30 | 43.2 | 1103A-33G | 3 | 105*127 | 3.3 | 7.9 | 211 | 1500*750*1100 | 800 |
| ZY-36GF | 36 | 45 | 64.8 | 1103A-33TG1 | 3 | 105*127 | 3.3 | 7.9 | 211 | 1550*750*1180 | 920 |
| ZY-50GF | 50 | 62.5 | 90 | 1103A-33TG2 | 3 | 105*127 | 3.3 | 7.9 | 215 | 1550*750*1180 | 1050 |
| ZY-50GF | 50 | 62.5 | 90 | 1104A-44TG1 | 4 | 105*127 | 4.4 | 8 | 208 | 1800*750*1180 | 1100 |
| ZY-64GF | 64 | 80 | 115.2 | 1104A-44TG2 | 4 | 105*127 | 4.4 | 8 | 208 | 1850*780*1200 | 1150 |
| ZY-64GF | 64 | 80 | 115.2 | 1104C-44TAG1 | 4 | 105*127 | 4.4 | 8 | 211 | 1850*780*1200 | 1250 |
| ZY-80GF | 80 | 100 | 144 | 1104C-44TAG2 | 4 | 105*127 | 4.4 | 8 | 205 | 1950*800*1200 | 1250 |
| ZY-80GF | 80 | 100 | 144 | 1104D-E44TAG2 | 4 | 105*127 | 4.4 | 8 | 216 | 1950*800*1200 | 1250 |
| ZY-110GF | 110 | 137.5 | 198 | 1106A-70TG1 | 6 | 105*135 | 7.01 | 18 | 199 | 2500*950*1450 | 1350 |
| ZY-120GF | 120 | 150 | 216 | 1106A-70TAG2 | 6 | 105*135 | 7.01 | 16.5 | 208 | 2600*950*1450 | 1450 |
| ZY-140GF | 140 | 175 | 252 | 1106A-70TAG3 | 6 | 105*135 | 7.01 | 16.5 | 206 | 2700*950*1450 | 1700 |
| ZY-160GF | 160 | 200 | 288 | 1106A-70TAG4 | 6 | 105*135 | 7.01 | 16.5 | 220 | 2800*950*1450 | 2100 |
| ZY-160GF | 160 | 200 | 288 | 1506A-E88TAG1 | 6 | 112*149 | 8.8 | 41 | 200 | 3000*1000*1700 | 2100 |
| ZY-180GF | 180 | 225 | 324 | 1506A-E88TAG2 | 6 | 112*149 | 8.8 | 41 | 200 | 3000*1000*1700 | 2100 |
| ZY-200GF | 200 | 250 | 360 | 1506A-E88TAG3 | 6 | 112*149 | 8.8 | 41 | 200 | 3100*1000*1700 | 2150 |
| ZY-240GF | 240 | 300 | 432 | 1506A-E88TAG5 | 6 | 112*149 | 8.8 | 41 | 198 | 3100*1000*1700 | 2150 |
| ZY-280GF | 280 | 350 | 504 | 2206C-E13TAG2 | 6 | 130*157 | 12.5 | 40 | 209 | 3250*1200*2000 | 3200 |
| ZY-320GF | 320 | 400 | 576 | 2206C-E13TAG3 | 6 | 130*157 | 12.5 | 40 | 206 | 3350*1200*2000 | 3300 |
| ZY-360GF | 360 | 450 | 648 | 2506C-E15TAG1 | 6 | 137*171 | 15.2 | 62 | 216 | 3450*1200*2050 | 3500 |
| ZY-400GF | 400 | 500 | 720 | 2506C-E15TAG2 | 6 | 137*171 | 15.2 | 62 | 211 | 3450*1200*2100 | 3760 |
| ZY-480GF | 480 | 600 | 864 | 2806C-E18TAG1A | 6 | 145*183 | 18.1 | 62 | 216 | 4100*1600*2200 | 4600 |
| ZY-520GF | 520 | 650 | 936 | 2806A-E18TAG2 | 6 | 145*183 | 18.1 | 62 | 202 | 4200*1600*2200 | 4800 |
| ZY-600GF | 600 | 750 | 1080 | 4006-23TAG2A | 6 | 160*190 | 22.9 | 113 | 202 | 4500*1800*2300 | 5500 |
| ZY-640GF | 640 | 800 | 1152 | 4006-23TAG3A | 6 | 160*190 | 22.9 | 113 | 210 | 4600*1800*2300 | 5500 |
| ZY-720GF | 720 | 900 | 1296 | 4008TAG1A | 8 | 160*190 | 30.5 | 153 | 206 | 4800*2100*2500 | 7700 |
| ZY-800GF | 800 | 1000 | 1440 | 4008TAG2A | 8 | 160*190 | 30.5 | 153 | 214 | 4900*2100*2500 | 8000 |
| ZY-900GF | 900 | 1125 | 1620 | 4008TAG2 | 8 | 160*190 | 30.5 | 165 | 202 | 4900*2100*2500 | 8000 |
| ZY-1000GF | 1000 | 1250 | 1800 | 4012-46TWG2A | 12 | 160*190 | 45.8 | 177 | 212 | 4950*2200*2550 | 8500 |
| ZY-1100GF | 1100 | 1375 | 1980 | 4012-46TWG3A | 12 | 160*190 | 45.8 | 177 | 212 | 4950*2200*2550 | 8700 |
| ZY-1200GF | 1200 | 1500 | 2160 | 4012-46TAG2A | 12 | 160*190 | 45.8 | 177 | 200 | 5050*2200*2550 | 9100 |
| ZY-1360GF | 1360 | 1700 | 2448 | 4012-46TAG3A | 12 | 160*190 | 45.8 | 177 | 208 | 5050*2200*2550 | 9500 |
| ZY-1480GF | 1480 | 1850 | 2664 | 4016TAG1A | 16 | 160*190 | 61.1 | 237 | 205 | 5700*2800*3100 | 13500 |
| ZY-1480GF | 1480 | 1850 | 2664 | 4016-61TRG1 | 16 | 160*190 | 61.1 | 237 | 201 | 5700*2800*3100 | 13500 |
| ZY-1600GF | 1600 | 2000 | 2880 | 4016TAG2A | 16 | 160*190 | 61.1 | 237 | 209 | 5800*2800*3100 | 14000 |
| ZY-1600GF | 1600 | 2000 | 2880 | 4016-61TRG2 | 16 | 160*190 | 61.1 | 237 | 205 | 5800*2800*3100 | 14000 |
| ZY-1800GF | 1800 | 2250 | 3240 | 4016-61TRG3 | 16 | 160*190 | 61.1 | 237 | 205 | 5900*2800*3100 | 15700 |



康明斯船用系列 柴油发电机组(50Hz)

CUMMINS MARINE SERIES(50HZ)

品牌介绍 / Brand

康明斯船用发电机组选用康明斯船用柴油机为动力,功率范围30kW-1000kW(37.5KVA-1250KVA),可选配马拉松、斯坦福、孚日等国内外知名品牌发电机。该系列发电机组质量优异,可靠性高,可提供柴油机国际防止空气污染证书以及CCS、BV船检证书。广受用户好评。

Cummins marine generator powered by Cummins marine diesel engine,power range from 30 kw to 1000 kw(37.5 KVA-1250 KVA),We have marathon,Stanford,Sunvim and other famous brands alternators to meet your demands.This series of genset is of excellent quality and high reliability,We can provide international air pollution-prevented certification and the certificate of CCS, BV classification survey,which is praised by our customers.

| | |
|-------------|--------------------|
| 标准配置 | Standard equipment |
| 可选配置 | Optional equipment |

标准配置

发动机
发电机
智能控制屏
钢式底架

Standard equipment

Diesel engine
Alternator
Digital control panel
Steel base frame

可选配置

静音箱
船用消声器
水套加热器
自动并机控制系统

Optional equipment

Sound proof
Marine silencer
Water heater
Automatic parallel synchronizing control system

规格参数 / Specifications

| 机组型号 (Model) | 功率Power KW KVA | | 频率/电压 Fre / Volt | 发动机型号 Engine model | 发动机功率 Engine Power | 缸数 Cylinder | 缸径*行程 Bore*Stroke | 排气量L Displacement | 油耗g/kw.h Consumption | 尺寸mm SIZE | 重量Kg Weight |
|------------------|-------------------|-------|---------------------|-----------------------|-----------------------|----------------|----------------------|----------------------|-------------------------|----------------|----------------|
| ZY30JW | 30 | 37.5 | 50/400 | 4BTA3.9-GM47 | 47/1500 | 4 | 102*102 | 3.9 | 6.39 | 1650*850*1270 | 760 |
| ZY40JW | 40 | 50 | 50/400 | 4BTA3.9-GM47 | 47/1500 | 4 | 102*102 | 3.9 | 10.02 | 1740*850*1270 | 800 |
| ZY50JW | 50 | 63 | 50/400 | 6BT5.9-GM83 | 83/1500 | 6 | 102*120 | 5.9 | 12.47 | 1900*895*1300 | 1000 |
| ZY64JW | 64 | 80 | 50/400 | 6BT5.9-GM83 | 83/1500 | 6 | 102*120 | 5.9 | 15.96 | 1900*895*1300 | 1100 |
| ZY75JW | 75 | 93.75 | 50/400 | 6BT5.9-GM83 | 100/1500 | 6 | 102*120 | 5.9 | 18.71 | 1920*895*1300 | 1250 |
| ZY90JW | 90 | 112.5 | 50/400 | 6BTA5.9-GM100 | 100/1500 | 6 | 102*120 | 5.9 | 22.45 | 1995*895*1300 | 1300 |
| ZY100JW | 100 | 125 | 50/400 | 6CT8.3-GM115 | 115/1500 | 6 | 114*135 | 8.3 | 24.94 | 2110*860*1360 | 1650 |
| ZY120JW | 120 | 150 | 50/400 | 6CTA8.3-GM155 | 155/1500 | 6 | 114*135 | 8.3 | 29.93 | 2110*860*1360 | 1700 |
| ZY150JW | 150 | 187.5 | 50/400 | 6LTAA8.9-GM200 | 200/1500 | 6 | 114*145 | 8.9 | 31.8 | 2210*860*1400 | 1870 |
| ZY180JW | 180 | 225 | 50/400 | 6LTAA8.9-GM200 | 200/1500 | 6 | 114*145 | 8.9 | 38.16 | 2210*860*1400 | 1890 |
| ZY200J | 200 | 250 | 50/400 | NTA855-DM | 240/1500 | 6 | 140*152 | 14 | 48.94 | 2760*995*1790 | 3100 |
| ZY200JW | 200 | 250 | 50/400 | N855-DM | 240/1500 | 6 | 140*152 | 14 | 48.94 | 2760*995*1790 | 3100 |
| ZY250J | 250 | 313 | 50/400 | NTA855-DM | 284/1500 | 6 | 140*152 | 14 | 61.18 | 2760*995*1790 | 3180 |
| ZY250JW | 250 | 313 | 50/400 | N855-DM | 284/1500 | 6 | 140*152 | 14 | 61.18 | 2760*995*1790 | 3180 |
| ZY280J | 280 | 350 | 50/400 | NTA855-DM | 317/1500 | 6 | 140*152 | 14 | 68.52 | 2998*995*1790 | 3250 |
| ZY280JW | 280 | 350 | 50/400 | N855-DM | 317/1500 | 6 | 140*152 | 14 | 68.52 | 2998*995*1790 | 3250 |
| ZY300J | 300 | 375 | 50/400 | KTA19-DM | 336/1500 | 6 | 159*159 | 19 | 44.8 | 3170*1000*1905 | 3750 |
| ZY320JW | 320 | 400 | 50/400 | K19-DM | 358/1500 | 6 | 159*159 | 19 | 49.5 | 3170*1000*1905 | 3750 |
| ZY350J | 350 | 438 | 50/400 | KTA19-DM | 403/1500 | 6 | 159*159 | 19 | 49.5 | 3170*1000*1905 | 3800 |
| ZY350JW | 350 | 438 | 50/400 | K19-DM | 410/1500 | 6 | 159*159 | 19 | 49.5 | 3170*1000*1905 | 3800 |
| ZY400J | 400 | 500 | 50/400 | KTA19-DM | 448/1500 | 6 | 159*159 | 19 | 54.2 | 3170*1000*1905 | 3950 |
| ZYJ400JW | 400 | 500 | 50/400 | K19-DM | 448/1500 | 6 | 159*159 | 19 | 54.2 | 3170*1000*1905 | 3950 |
| ZY500J | 500 | 625 | 50/400 | KT38-DM | 560/1500 | 12 | 159*159 | 38 | 78.5 | 3950*1500*2500 | 6200 |
| ZY600J | 600 | 750 | 50/400 | KTA38-DM | 664/1500 | 12 | 159*159 | 38 | 87.5 | 4050*1500*2680 | 6550 |
| ZY650J | 650 | 813 | 50/400 | KTA38-DM | 746/1500 | 12 | 159*159 | 38 | 78.5 | 4050*1500*2680 | 6980 |
| ZY700JW | 700 | 875 | 50/400 | K38-DM | 814/1500 | 12 | 159*159 | 38 | 103.7 | 4100*1500*2700 | 6980 |
| ZY800J | 800 | 1000 | 50/400 | KTA38-DM | 880/1500 | 12 | 159*159 | 38 | 109.4 | 4100*1500*2700 | 7000 |
| ZY800JW | 800 | 1000 | 50/400 | K38-DM | 880/1500 | 12 | 159*159 | 38 | 109.4 | 4100*1500*2700 | 7000 |
| ZY1000JW | 1000 | 1250 | 50/400 | K50-DM | 1092/1500 | 12 | 159*159 | 38 | 141.7 | 4250*1500*2700 | 7500 |



柴油发电机组

移动电源车 系列

功率范围：**68KW~650KW**

品牌介绍 / Brand

ZYPOWER中彦动力移动电源车系列柴油发电机组采用原装进口发动机，选配马拉松、斯坦福、法拉第等国际知名品牌发电机，具体高稳定性、高可靠性、极大程度保证设备连续运行，为客户提供高品质的后备电源。电源车主要有汽车底盘、柴油发动机、发电机、控制配电系统、车厢、降噪系统、支撑装置、电缆收放装置、排烟消声系统、供油系统及配套设施等组成。

ZYPOWER Automobile power station series select the original imported engine and world famous bands of alterator (Marathon,Stanford or Farady)which has high stability and reliability.The continuous running of the Gensets could be strongly guaranteed,The vehicle is mainly composed of automobile chassis,diesel engine,alternator,distribution control system,carriage,noise reduction system,support device,cable reel,exhaust and silencing system,fuel supply system and supporting facilities,etc.

噪音低

独特的隔音处理专利技术，极大程度在保障功率的情况，使得噪声在中心距离箱体7米处仅为78dB

Low noise level:Unique patented technology of acoustic processing to ensure the output power and reduce the noise level to 78Db at 7m

智能化电站

采用我司独立自主开发的智能控制系统，具有智能并网发电、多机并联运行、自动转换、互为备用控制等，并可根据使用情况与项目相关设备进行联动控制

Intelligent power station:Adopts with the intelligent control system which developed by ourselves,has the function of automatic synchronizing with the power grid,multimachine synchronizing,automatic transfer,primarily and standby exchange control and so on, and could fulfill linkage control with related equipments of the project according to the operation condition

规格参数 / Specifications

| 底盘型号 Chassis Type | 载重箱体长度 Load & Length | VPDM101 68-104 | VPDM102 120-200 | VPDM103 220-320 | VPDM104 360-500 | VPDM105 300-500 | VPDM106 540-650 |
|----------------------|-------------------------|-------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| 依维柯 NJ5056XXYNS | 2.095T 内4500 | — | — | — | — | — | — |
| 解放 CA1163P7K2L3E | 9.035T 长7600 | — | — | — | — | — | — |
| 庆铃 NKR77PLNACJAKY | 3.5T 内5050 | — | — | — | — | — | — |
| 庆铃 FVR34P2 | 7.1T 长7600 | — | — | — | — | — | — |
| 庆铃 FVR34P2裙板 | 7.1T 长7600 | — | — | — | — | — | — |
| 庆铃 FVZ34Q | 12T 长7600 | — | — | — | — | — | — |
| 北奔 ND1256B50J | 13.37T 长8500 | — | — | — | — | — | — |
| 东风 EQ5080XXYG9AD | 2.99T 内5750 | — | — | — | — | — | — |
| 东风 DFL5120XXYB1 | 4.7T 内7500 | — | — | — | — | — | — |
| 东风 EQ5168XXYK1 | 7.99T 内7200 | — | — | — | — | — | — |
| 东风 DFL5253XXYAX | 13.99T 内9600 | — | — | — | — | — | — |
| 庆铃 NKR77PLPACJAX | 4T 内5050 | — | — | — | — | — | — |
| 庆铃 KUL5100XTPAR | 4.8T 内7012 | — | — | — | — | — | — |
| 庆铃 FVR34P2X | 7.1T 内7120 | — | — | — | — | — | — |
| 庆铃 FVZ34VX | 11.2T 内9350 | — | — | — | — | — | — |
| 庆铃 FVZ34QX | 12T 内7120 | — | — | — | — | — | — |
| 北奔 ND5160X | 7.27T 内7340 | — | — | — | — | — | — |



柴油发电机组

照明车机组 系列

品牌介绍 / Brand

- ZYPOWER 中彦动力 照明车 采用高品质、低排放、低油耗的发电机组，为灯具提供可靠的持续电源。
- 灯杆镀锌、箱体喷漆，灯具防护等级IP65，独立可调支脚，可适应各种恶劣的使用环境。防雨、放音，抗风等级为8级。
- 手动或无线遥控调节灯杆高度，灯杆旋转359° 范围内、照射角度90° 范围内可调。并且每个灯具独立控制。
- 采用大容量油箱，一次注满燃油持续工作超过48小时；提供市电接入接口，在有市电的场所，也可接通市电电源实现长时间照明。
- 提供2个外接防护等级为IP44的外供电源插座。
- 操作简易、标识清晰。

*ZYPOWER Lighting vehicle series the Gensets with high quality,low emission and fuel consumption to provide reliable continuous power supply to the light.

*Galvanized lamppost,power coating canopy.The protection level of the lamp IS IP65.With adjustable support which could be accommodated the atrocious conditions,weatherproof and soundproof.Wind resistance level is 8.

*The height of lamppost could be adjusted manually or automatically.Maximum swivel angle of the lamppost is 359 degree.The lighting angle of the lamp could be adjusted within 90degree. And every lamp could be controlled separately.

*Tuse fuel tank with big capacity which can fulfill 48hrs running of the Gensets.Provide the interface of mains supply.The lamp could be also connected with the mains supply for long time lighting.

*Provide 2 External power sockets which are IP44.

*Simple operation,clear indication.

规格参数 / Specifications

| 底盘型号 Chassis Type | VPK8-L-4-1000-A | VPZ8-L-4-1000-A | VPP8-L-4-1000-A |
|----------------------|-----------------|-----------------|-----------------|
| 长度 (mm) | 2800 | | |
| 宽度 (mm) | 1550 | | |
| 高度 (mm) | 2300 | | |
| 灯杆高度 (完全伸展) | 9m | | |
| 重量 (kg) Weight | 1150kg | | |
| 底盘型号 Chassis Type | VPK8-L-4-1000-M | VPZ8-L-4-1000-M | VPP8-L-4-1000-M |
| 长度 (mm) | 2300 | | |
| 宽度 (mm) | 1500 | | |
| 高度 (mm) | 2300 | | |
| 灯杆高度 (完全伸展) | 5m | | |
| 重量 (kg) Weight | 1000kg | | |



柴油发电机组

集装箱电站 系列

功率范围：68KW~2400KW

品牌介绍 / Brand

ZYPOWER 中彦动力集装箱电站系列柴油发电机采用原装进口发动机，选配马拉松、斯坦福等国际知名品牌发电机，具有高稳定性、高可靠性，极大程度保证设备联系运行，为客户提供高品质的后备电源，集装箱电站根据需要可配套安装柴油发电机组、排烟消声系统、邮箱、自动加油装置、控制系统、并机并网柜、ATS柜、开关柜、静音降噪材料、照明系统及其他辅助配套装置，机组功率可为68—2400KW。

ZYPOWER containerized power station series select the original imported engine and world famous bands of alternator (Marathon&tamford)which has high stability and reliability. The continuous running of the Gensets could be strongly guaranteed.

The containerized power station could install with complete diesel Generating ses,exhaust silencing system,fuel tank,automatic fuel filling device,control system,synchronizing cabinet,ATS cabinet,switch cabinet,noise reduction material,lighting system and other auxiliary devices,The power range can be 68-2400KW.

噪音低

独特的隔音处理专利技术，极大程度在保障功率的情况，使得噪声在中心距离箱体7米处仅为78ddB

Easy operate and maintenance:Integrative design and layout,humanized operation interface which has the lowest maintenance cost

强劲动力

原装进口发动机、发电机组，高品质的保障

Strong power:Original imported engines,high quality assurance

智能化电站

采用我司独立自主开发的智能控制系统，具有智能并网发电、多机并联运行、自动转换、互为后备控制等，并可根据使用情况与项目相关设备进行联动控制

Intelligent power station:Adopts with the intelligent control system which developed by ourselves,has the function of automatic synchronizing with the powwe grid,multimachine synchronizing,automatic transfer,primarily and standby exchange control and so on, and could fulfill linkage control with related equipments of the project according to the operation condition

规格参数 / Specifications

| 规格 Genset Model | 机组功率 Prime Power | 电站尺寸 (长×宽×高) Dimension(mm) | 备注 Weight(Kg) |
|--------------------|---------------------|-------------------------------|------------------|
| 20G | 500-640 | 6038×2438×2591 | |
| 20HQ | 580-818 | 6038×2438×2896 | |
| 40HG | 640-1800 | 12192×2438×2896 | |
| 45HQ | 2000-2400 | 13982×2438×2896 | |

根据机组可设计制作特殊规格集装箱，实际配置需根据机组和配套要求确定集装箱尺寸和消声器安装位置。



柴油发电机组

防音箱VMP 系列

功率范围：500KW

品牌介绍 / Brand

ZYPOWER 中彦动力防音箱采用专用箱体内置成套发电机组，拥有自主的防音专利技术，总体结构紧凑，美观方正；回流式风道；高性能耐老化阻燃型隔音、吸音材料；内置式阻抗复合式消声器；非常有效的抑制噪音，噪音可降至70dBA以下。

ZYPOWER soundproof canopy install the Genset into special housing built canopy,use the soundproof technology which is developed by ourselves. The overall structure is compact,square layout,with great appearance,using turn flow air duct,high performance antiageing flame retarded sound insulation and absorbing material.Built-in impedance compound silencer,which could restrain the noise effectively.The noise can be reduced to less than 70dBA.

规格参数 / Specifications

| 产品型号 Product Model | 适用型号 Product Model | 电站尺寸 (长×宽×高) Dimension(mm) | 重量 Weight(Kg) |
|-----------------------|---|-------------------------------|------------------|
| VMP101 | VPC25/VPC38/VPC50/VPC63 | 2800×1060×1700 | 1280~1440 |
| VMP102 | VP85/VP100/VP130/VPC80/VPC93 VPC100/VPC112/VPC130 | 3060×1250×1750 | 2000~2300 |
| VMP103 | VP150/VP183/VP200/VP250 VPD200/VPC150/VPC188/VPC200 VPC225/VPC250 | 3900×1300×2000 | 2500~3200 |
| VMP104 | VP325/VP375/VP400/VP450 VPD275/VPD312/VPC225/VPC250/VPC270 VPC285/VPC312/VPC350/VPC375/VPC400 | 4500×1400×2150 | 3800~4800 |
| VMP105 | VP500/VP575/VPC450/VPC500 | 5000×1400×2400 | 5100~5400 |
| VMP106 | VPD375/VVPD400/VPD450/VPD500 | 4600×1600×2250 | 4100~5000 |
| VMP107 | VP625/VPD575/VPD625/VPC575/VPC625 | 5300×1800×2650 | 5400~6000 |

开关柜

Switch cabinet

VPK系列

ZYPOWER 中彦动力 开关柜采用施耐德、杭州之江断路器品牌。标准GGD柜结构，型材构架，接线简单，使用方便，外形美观，可根据用户要求选用开关品牌。

The switch cabinet of ZYPOWER select the world famous brand of Schneider and SK from HSW in China. Standard GGD structure, structure of sections, simple wiring, convenient operation and nice appearance, could select different brands of switches according to the customer requirement.



并机柜

Synchronizing control cabinet

VPB系列

ZYPOWER 中彦动力 并机柜采用全自动控制并机系统，含GAC同步模块，GAC 功率分配模块。采用施耐德、杭州之江。标准GGD柜结构，型材构架，银触点、切换时间短，满足各种电力场合的要求。

The Synchronizing control cabinet of ZYPOWER selects the automatic synchronizing control system, include the GAC synchronization control module and GAC power distribution module. Brand of Switch: Schneider and HSW. Standard GGD structure, structure of sections, short switch time, could fulfill various requirement of power situation.



自动切换开关柜

ATS

VPA系列

ZYPOWER 中彦动力 自动切换开关柜（ATS）采用法国溯高美、扬州爱斯凯转换开关。标准GGD柜结构，型材构架，银触点、切换时间短，满足各种电力场合的要求。

ATS of ZYPOWER select the world famous brand of changeover switch such as Socomec from France and SK from Yangzhou China. Standard GGD structure, structure of sections, short switch time, could fulfill various requirement of power situation.



PT柜

PT cabinet

KYN28-PT

ZYPOWER 中彦动力 PT柜采用高品质电压互感器保证电压测量精准，配置相应的熔断器、隔离刀闸、继电保护及避雷器。标准GGD柜结构，型材构架，接线简单，使用方便，外形美观。

The PT cabinet of ZYPOWER selects the voltage transformer with high quality to ensure the accurate voltage measurement, relative fuse, isolating switch, relay protection and surge arrester. Standard GGD structure, structure of sections, simple wiring, convenient operation and nice appearance.

直流电源屏

DC power supply panel

DC110V-36AH

ZYPOWER 中彦动力 高频开关直流电源系统采用第三代智能高频开关电源模块，各功能单元均为具有CPU的智能化单元，具有自诊断能力；单元与单元、单元与监控器之间全部是数字通讯且输入输出电气全隔离，环境适应能力强。

High frequency DC Power supply panel of ZYPOWER use the 3rd Generation intelligent high frequency switch power module. Every functional unit is the intelligent unit with CPU which has the function of automatic fault diagnosis. Strong environment adaptiveness. All of them are digital communication and full isolated electric input-output between the units, and units to monitor.



高压开关柜

High Voltage Switchgear

KYN28-630A

ZYPOWER 中彦动力 系列高压开关柜采用ABB公司生产的VD4真空断路器，主绝缘采用复合绝缘设计，安全满足“五防要求”。柜体外壳选用进口敷铝锌板，抗氧化，抗腐蚀；采用组装式结构，由拉铆螺钉和高强度的螺栓连接而成，具有较高的机械强度，适用各种电力环境。

High voltage switchgear select the VD4 vacuum circuit breaker of ABB. compound insulation design was used in the major insulation, could fulfill the "Five-protection" requirement. Aluminum Zinc plate is selected in the Cabinet enclosure which is anti-oxidant anti-corrosion. Use modular structure which is connected by blind-riveting bolt and high strength bolt. This kind of structure has high mechanical strength and suitable for various power situation.



接地电阻柜

Grounding resistor cabinet

VP-GNR606Ω/10A

ZYPOWER 中彦动力 系列接地电阻柜专用于高压发电机中性点采用高电阻接地的成套装置。电压等级主要为6kv至20kv。当定子发生一点接地时，可限制接地电流在很小的数值，并有效抑制电弧接地暂态过电压。

The earth resistance cabinet of ZYPOWER specially applied for the complete equipments of high voltage Generator neutral point which is high resistance ground faults.



一诺千金，在整个使用周期中始终提供无忧的全面服务

As good as gold in the entire life cycle
Always provide a hassle-free full-service

售前服务/Service Before Sale

提供售前技术支持
协助机房设计、布置，安装建议
帮助选择机型、容量及功能

Provide pre-sale technical support
Help to dispose the machine house and provide suggestions for installation
Help to choose genset model, capacity and function

售后服务/After Service

设备安装、调试及电气联接
机房环保工程
余热利用工程
消防检验测试
用户操作培训
指导设备保养、维护及简易故障排除
快速提供零配件
受委托管理设备

Electric connection commission and installation of equipments
Environment protection project
Residual heat utilization project
Fire protection inspect and test
Maintenance guidance
Fault remedy and difficult problem explanation
Prompt&le supply of spare parts, timely repair
Gensets mandatory management

服务承诺/Service Guarantee

建立用户档案，跟踪服务，定期巡访定期用户操作人员集中培训
节假日或特殊日可派人协助值守
世界名厂原厂技术支持及零配件支持
接报修30分钟作出回复，2小时派出人员一般故障处理2小时，重大故障8小时

Set up the customer record, follow-up service and visit periodically
Provide the training to the operator of users periodically
Can arrange personnel to help the operation during holiday or special day
Technical support and spare parts support from the world famous manufacturers
Respond within 30 minutes after receiving the claim for repair from the customer, the service person will be sent within 2 hours
Can manage the common fault within 2 hours, and severe malfunction in 8 hours

培训/Train

用户现场操作、保养培训
工厂集中技能提升培训
原厂指导培训

On-site training of maintenance and operation
Technique upgrade training in the factory
Guidance and training in the factory


配套工程/Supporting engineering

发电机房设计，机组安装、联动调试环保降噪工程，热回收利用工程
并机并网(市电、发电)工程

Genset room design, installation, and commissioning
Environment protection and soundproof project, heat recovery project
Paralleling and synchronization (main power, genset power) project

服务流程

Service Process



零配件服务

Parts Service

ZYPOWER 中彦动力 发电机组作为专业化程度非常高的设备，需要非常专业的人员进行定期维护与保养。沃尔奔达作为专业的制造与服务商，有一支非常专业的服务队伍。以低廉的收费，代为用户进行长期性的定期保养。

As the special equipment with high specification degree, generating sets should be maintained by professional operators. As a professional manufacturer and service agent of generating sets, ZYPOWER has a very professional service team. Provide regular termly maintenance with low charges.

保养的组成部分

Content of Maintenance

设备管理和控制

Genset management and control

运行环境监控

Monitoring of running condition

保养与维修实践

Maintenance & Repair practice

系统的保养管理

System maintenance and management



预防性保养的益处

Benefit of preventive maintenance

提升设备使用利润

Improve the operation profit of equipments

有助于成本控制

Help to cost control

控制服务周期

control the service cycle

延长设备寿命

Extend the life of the facility

最大限度缩短停机时间

Shorten maximizely the emergency stop time

增加工作的可控性

Increase the work controllability

增加转售价值

Increase the resale value



租赁服务

Rental Service

ZYPOWER 中彦动力 公司针对不同的市场需求提出全新的服务模式，提供多种融资租赁渠道及合作方式，根据用户的实际需求打造全新的租赁方式。通过双方的合作共赢模式能够有效解决该设备占用大量资金的问题，同时能够将这部分资金盘活，增加资金的使用率，提高收益，降低资金投入风险。另外通过柴油发电机组制造商的专业运营管理，有效降低运行维护成本和提高应急突发事件处理能力，为数据中心设备的稳定运行提供坚实的保障基础。

ZYPOWER provide a whole new service mode according to different market demand. We provide different financial leasing channels and cooperative mode, create entirely new lease mode. The problem of the Genset would occupy a very great amount of capital could be solved effectively through win-win cooperation by both parties. The associated capital will be revitalized. The efficiency ratio and profit will be improved. The investment risk will also be reduced. Based on the professional operational management of the diesel Genset manufacturer, the maintenance cost will be effectively reduced and the ability to deal with occasional events will be improved. This will provide solid support foundation for the stable running of equipments in the data centre

全新的柴油发动机组

Brand new diesel generating sets

各种品牌的动力系统组合


Various brands of Power system

全新服务托管模式

New service trusteeship mode

集约化电站管理方式

Intensive management of power station



客户服务

Customer Service



畅享沟通，全面的交流与培训 为客户提供更完善的服务

Enjoy communication, exchanges and training
More comprehensive services with customers

用户现场操作、保养培训

On-site training of maintenance and operation

工厂集中技能提升培训

Technique upgrade training in the factory

原厂指导培训

Guidance and training in the factory

发电机房设计,机组安装、联动调试

Genset room design, installation, and commissioning

环保降噪工程,热回收利用工程

Environment protection and soundproof project, heat recovery project

并机并网(市电、发电)工程

Paralleling and synchronization (main power, genset power) project



服务网络

Service Network



国内主要销售服务网点

Major domestic sales service network

合作伙伴/ Cooperative partner

